

DECOREX ACRYLIC DISTEMPER

DECORATIVE ACRYLIC DISTEMPER FOR
ENHANCED INTERIOR AESTHETICS

DECOREX Acrylic Distemper combines decorative appeal with durable protection to deliver beautiful, long-lasting walls. Its smooth finish, excellent coverage and easy application make it the perfect choice for modern interiors.



-  **DECORATIVE FINISH**
Enhances interior walls with a smooth and elegant look.
-  **DURABLE**
Provides durable protection and long-lasting performance.
-  **EASY APPLICATION**
Smooth consistency for quick and effortless application.
-  **GOOD COVERAGE**
Excellent coverage ensures a uniform and rich finish.

1. WHY CHOOSE DECOREX ACRYLIC DISTEMPER?

-  **Decorative Finish**
Adds a beautiful, smooth and attractive look to interior walls.
-  **Durable**
Resists normal wear and tear, keeping walls looking fresh for longer.
-  **Easy Application**
User-friendly and hassle-free application for professional results.
-  **Good Coverage**
High opacity and excellent hiding power for superior coverage.

2. IDEAL FOR

-  **Interior Decoration**
Ideal for all types of interior wall surfaces.
-  **Feature Walls**
Highlights and enhances accent and feature areas.
-  **Commercial Spaces**
Suitable for offices, shops and retail environments.
-  **Hospitality**
Perfect for hotels, restaurants and other hospitality spaces.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Acrylic Distemper
- Finish : Matt
- Colour : As per shade card
- Viscosity : 90 – 110 KU @ 25°C
- Solids by Volume : 40 ± 2%
- Drying Time (Touch Dry) : 30 – 60 min
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 4 – 6 hrs
- Coverage : 80 – 100 sq.ft./litre/coat*
- No. of Coats : 2 – 3 Coats
- Thinner : Clean Water
- Packaging : 1L, 4L, 10L, 20L

*Coverage may vary depending on surface type, texture and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Appearance	Smooth, Uniform
Opacity	Excellent
Washability	Good
Water Resistance	Good
Alkali Resistance	Good
Fungus Resistance	Good
Flaking	No Flaking
VOC Content	Low VOC
pH Value	8.5 – 9.5
Coverage	80 – 100 sq.ft./litre/ /coat*

4. SURFACE PREPARATION & APPLICATION GUIDE

- 1 SURFACE PREPARATION**
 - Surface must be clean, dry and free from dust, dirt, grease, oil or loose paint.
 - Scrape off flaking paint and sand the surface smooth.
 - Fill cracks and holes with suitable putty and allow to dry.
- 2 PRIMING**
 - Apply suitable Acrylic Wall Primer for better adhesion and long lasting performance.
 - Allow primer to dry completely.
- 3 DILUTION**
 - Dilute distemper with clean water.
 - Normal dilution: 30 – 40% for first coat and 20 – 30% for subsequent coats.
- 4 APPLICATION**
 - Stir well before use.
 - Apply 2 – 3 coats using a roller, brush or spray.
 - Allow proper drying time between coats.
- 5 CLEANING**
 - Clean all tools and equipment with clean water immediately after use.

5. SAFETY FEATURES & PRECAUTIONS

-  Use in well-ventilated areas.
-  Wear protective gloves.
-  Avoid contact with eyes and skin.
-  Keep out of reach of children.
-  In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Refer to MSDS for complete safety information.

STORAGE PRECAUTIONS

-  Store in a cool, dry place away from heat and direct sunlight.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and extreme temperatures.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

-  Interior Decoration
-  Feature Walls
-  Commercial Spaces
-  Hospitality

