

DURACORE ENAMEL

PREMIUM PERFORMANCE COATING

SUPERIOR PROTECTION. RICH GLOSS FINISH.

Duracore Enamel delivers exceptional strength, durability, and a brilliant glossy finish that stands the test of time. Engineered for metal, it eliminates the need for a primer while ensuring superior adhesion and long-lasting protection. With its advanced fast-drying formula, complete two coats in a single day and enjoy a flawless, rich gloss finish.



4-YEAR RUST PROTECTION

Reliable protection against rust and corrosion for up to 4 years.



SUPERIOR STRENGTH & DURABILITY

Forms a tough, hard-wearing film that resists impact, abrasion and wear.



FAST DRYING FORMULA

Dries 25% faster than standard enamels – complete two coats in a day.



PRIMER-FREE APPLICATION

Direct-to-metal application with excellent adhesion.



AVAILABLE PACK SIZES



1. WHY CHOOSE DURACORE ENAMEL?



4-Year Rust Protection Warranty

Advanced rust-inhibiting technology provides long-term protection for metal surfaces.



Superior Strength & Durability

High-performance enamel that offers excellent resistance to impact, abrasion, and harsh weather conditions.



Fast-Drying Performance

Dries 25% faster than standard enamels, allowing two coats to be completed within a single day.



Primer-Free Application

Specially formulated for strong adhesion on metal – no primer required.



Rich, Glossy Finish

Delivers a smooth, rich gloss that enhances the beauty and life of your metal surfaces.

2. IDEAL FOR



Interior Metal Substrates

Ideal for metal doors, frames, railings and interior structures.



Exterior Metal Structures

Perfect for gates, grills, railings, pipelines and outdoor metal surfaces.



Metal Furniture & Fixtures

Gives long-lasting beauty to chairs, tables, cabinets and metal décor.



General Metal Surfaces

Suitable for industrial equipment, machinery, shelves and more.

3. PRODUCT DETAILS

TECHNICAL INFORMATION

- **Product Type**
Premium Enamel Paint
- **Finish**
Smooth Rich Gloss
- **Base**
Oil Based
- **Application**
Metal Substrates
- **Drying Time**
Dries 25% faster than standard (Surface Dry: 2 – 3 hours
Hard Dry: 6 – 8 hours)*
- **No. of Coats**
2 Coats Recommended
- **Coverage**
10 – 12 m²/L/coat*
- **Thinner**
Mineral Turpentine
- **Shelf Life**
36 months from date of manufacture
- **Pack Sizes**
250 ml, 500 ml, 1 L, 4 L, 10 L, 20 L

*Coverage and drying time may vary depending on surface, temperature and application method.

KEY BENEFITS



4-Year Rust Protection



Superior Strength & Durability



Fast-Drying Formula



Primer-Free Application



Smooth Rich Gloss Finish



Excellent Adhesion to Metal



Weather & Corrosion Resistant



Long-Lasting Beauty & Protection

4. HOW TO APPLY



1 PREPARE SURFACE

- Ensure the metal surface is clean, dry and free from loose rust, oil, grease, dust or old paint.
- Sand or wire brush if required and wipe clean.



2 APPLY PAINT

- Stir the enamel thoroughly before use.
- Apply an even coat using a brush, roller or spray equipment.
- Ensure uniform coverage.



3 FINISH

- Allow the first coat to dry completely.
- Apply the second coat for enhanced protection and rich gloss.
- Best results with 2 coats.

TIPS FOR BEST RESULTS

- ✓ Apply in a well-ventilated area.
- ✓ Ideal application temperature: 10°C – 40°C.
- ✓ Avoid painting in direct sunlight or extreme humidity.
- ✓ Use high-quality brushes, rollers or spray equipment.
- ✓ Close the container tightly after use.
- ✓ Allow sufficient drying time between coats.

5. SAFETY FEATURES & PRECAUTIONS



Wear gloves



Wear eye protection



Keep area well ventilated



Keep out of reach of children



Avoid inhalation of vapours



Do not dispose in drains

- Keep container tightly closed when not in use.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Refer to the Material Safety Data Sheet (MSDS) for complete safety information.

STORAGE PRECAUTIONS



- Store in a cool, dry place away from heat and direct sunlight.
- Keep containers tightly closed when not in use.
- Do not store near food, beverages or animal feed.
- Shelf life: 36 months from date of manufacture.

RECOMMENDED FOR

- ✓ Interior & Exterior Metal Surfaces
- ✓ Metal Doors, Windows & Frames
- ✓ Grills, Gates & Railings
- ✓ Metal Furniture & Fixtures
- ✓ Industrial Machinery & Equipment
- ✓ Pipelines & Structural Steel
- ✓ General Metal Applications

SCAN TO KNOW MORE



4-YEAR RUST PROTECTION



SUPERIOR STRENGTH & DURABILITY



FAST-DRYING FORMULA



PRIMER-FREE APPLICATION



SMOOTH RICH GLOSS



LONG-LASTING BEAUTY