

DURACORE

PREMIUM HEAVY-DUTY FLOOR RESIN

Duracore is a high-performance floor coating engineered with a water-based crosslinking acrylic emulsion. It provides exceptional durability, superior adhesion, and outstanding resistance to abrasion and daily wear—protecting your concrete surfaces for years.



TWO-YEAR WARRANTY



WATER-BASED FORMULA



STRONG ADHESION & DURABILITY

2. AREAS OF APPLICATION



EXTERIOR CONCRETE FLOORINGS



EXTERIOR CEMENT FLOORINGS

FEATURES AND BENEFITS



WATER-BASED CROSSLINKING ACRYLIC FORMULA

Environment-friendly formulation with excellent performance.



SUPERIOR ABRASION & WEAR RESISTANCE

Withstands heavy foot traffic, abrasion, and daily wear and tear.



EXCELLENT ADHESION

Bonds strongly with concrete and cement substrates for long-lasting protection.



TWO-YEAR PERFORMANCE WARRANTY

Dependable quality backed by a comprehensive 2-year warranty.

3. PRODUCT DETAILS

Type: Floor Coating (Water-Based)

Finish: Sheen

Colour: As per shade card

Packaging: 20 L

Shelf Life: 2 years

Coverage: 8 – 10 sq. m./L/coat*

*Coverage may vary depending on surface texture, porosity, and application method.

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Sheen Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Adhesion Strength	ASTM D 4541	> 1.5 MPa
Abrasion Resistance	ASTM D 4060	Excellent
Water Resistance	ASTM D 870	No blistering / No softening
Chemical Resistance	Internal Method	Resistant to mild chemicals, oils and detergents
VOC Content	As per BIS Standards	Low
Flash Point	IS 101 (Part 1)	Non-flammable
Application	—	Exterior Concrete & Cement Floors

4. APPLICATION METHOD



1. PREPARE SURFACE

Ensure the concrete or cement surface is clean, dry, and free of dust, oil, grease, or loose particles.



2. APPLY COATING

Apply an even coat of Duracore using a brush, roller, or sprayer according to the recommended spread rate.



3. ALLOW TO CURE

Let the coating dry completely under standard environmental conditions before subjecting it to traffic or heavy use.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for detailed information on safe handling and usage.



Store the container with the lid tightly closed in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures. Protect from direct sunlight and frost.


RECOMMENDED FOR



- ✓ Residential Spaces
- ✓ Commercial Buildings
- ✓ Industrial Floors
- ✓ Parking Areas
- ✓ Walkways & Driveways

HOW TO USE

- 1 Clean the surface and remove dust, oil, or loose particles.
- 2 Apply the coating as per recommended method.
- 3 Let it dry for 4–6 hours before subjecting to use.



SELF-LEVELING FINISH



HIGH STRENGTH FORMULA



CHEMICAL RESISTANT




IMPACT TOUGH



LONG LASTING PERFORMANCE



TWO-YEAR WARRANTY



WATER-BASED & LOW VOC