

Duracote

PREMIUM FLOOR ARMOR

Advanced formulation designed to provide superior protection and beauty to exterior concrete floors and pavers.



- WATER BASED
- LEAD-FREE* GUARANTEE
- NO ADDED LEAD, MERCURY OR CHROMIUM

*All COLORSOME products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



PAVER BLOCKS



CEMENT BLOCK FLOORS



STAMPED CONCRETE FLOORS



CEMENT TILES

2. FEATURES AND BENEFITS

- ✓ Pure acrylic based advanced formulation
- ✓ Provides superior protection and beauty
- ✓ Better sheen provides a vibrant finish to concrete floors
- ✓ High abrasion resistance for low wear
- ✓ Excellent adhesion to concrete substrates
- ✓ Water-based and environmentally friendly
- ✓ 2 Years Performance Warranty for film integrity*
- ✓ Comprehensive coverage on cemented paver blocks
- ✓ Low maintenance and easy cleaning
- ✓ All COLORSOME products contain no added Lead, Mercury, Arsenic or Chromium

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Chemical Base: Pure Acrylic Dispersion
- Solvent Type: Water-based
- Drying Time: Surface dry 30 min (at 30°C)



PARAMETER	TYPICAL VALUES
Sheen Level	Upto 50 at 60° GH
Theoretical Coverage	40 - 45 sq.ft/ltr for 2 coats on normal masonry surface
Dilution % (by vol.) Step 1	30 - 40% (Water)
Dilution % (by vol.) Step 2	10 - 20% (Water)
Recoating Period	4 - 6 HRS (at 25°C & 50% RH)
Performance Warranty	2 Years
Shelf Life	3 Years
Pack Sizes	1 ltr, 4 ltr, 20 ltr

4. APPLICATION METHOD



SURFACE PREPARATION

- **Fresh Painting (Unpainted):** For fresh concrete, allow to cure for at least 4 weeks. Ensure surface is free from damp, loose paint, dust, wax, grease, other contaminants. Wash with scrubbing brush; dry min. 4-6 hours. Moisture content must be less than 10%.
- **Repainting Surface:** Check existing paint film adhesion. Sand smooth or glossy surfaces to improve adhesion. Total old paint removal required if adhesion problems observed.



DILUTION & APPLICATION

- **Dilution:** Dilute Duracote with water only.
- **APPLICATION:** Strain material before use. Diluted paint to be used within 24 hrs. Depending on surface, third coat may be applied at 10-20% dilution for hiding.

STAGE 1 (FRESH/PREPAINT)

Dilution 30-40%. Viscosity 75-125 sec.

STAGE 2 (FRESH/REPAINT)

Dilution 10-20%. Viscosity 100-150 sec.



ADDITIONAL INFO & CARE

- Recoat period (at 25°C & 50% RH) is 4-6 hours.
- **Post Painting Curing:** Allow at least 48 hours for light foot traffic and 72 hours for light traffic movement at 30°C and higher temperatures.
- Curing time needs to be extended in high humidity, damp, or cold conditions. For best performance, allow complete 7 days curing before regular movement.
- Do not wash surface with wire brush. For best performance, ensure regular washing and cleaning. Avoid source of prolonged dampness.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the Material Safety Data Sheet (MSDS) for detailed safety measures.



Store container tightly closed, upright, in a cool, dry place out of reach of children.



Do not breathe vapor or spray. Wear a suitable nose pad during sanding & application.



Do not apply under extreme conditions of frost, dew, rain, fog or adverse weather.



Product is suitable for stable and rough substrates; use on loose, uncured or ash brickwork can lead to peeling.



Do not pour leftover paint down the drain or water.



Do not use over smooth, ceramic tiles, glossy surfaces, bituminous asphalt, or other water repellent surfaces.



Tint using COLORSOME machine colorants only. Do not over-thin.

STORAGE PRECAUTIONS



Store in a cool, dry place away from direct sunlight.



RECOMMENDED FOR



- ✓ Residences, Apartments
- ✓ Commercial Properties
- ✓ Sports Complexes
- ✓ Playgrounds

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 2 coat of Duracote evenly.
- 3 Let 8 dry for 4-6 hours before applying next coat.



STRONG ADHESION



HIGH ABRASION RESISTANCE



EASY CLEANING



WEATHER PROTECTION



LONG LASTING PERFORMANCE