

# Duraguard Emulsion

Premium Protective Finish



High Durability



Weather Resistant

## 1. AREAS OF APPLICATION



EXTERIOR WALLS



INTERIOR WALLS



CEILINGS



MASONRY

Suitable for exterior and interior surfaces such as walls, ceilings, masonry and more.

## 2. FEATURES AND BENEFITS

- ✓ Excellent weather resistance
  - ✓ Highly durable finish
  - ✓ Superior water repellency
  - ✓ UV protective properties
- ✓ Smooth premium finish
  - ✓ Long-lasting protection
  - ✓ Excellent washability
  - ✓ Easy application

## 3. PRODUCT DETAILS

### CHEMICAL PARAMETERS:

Acrylic Emulsion Dispersion

### PHYSICAL PARAMETERS:

- Colour and appearance
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 1.3 - 2 kg per sq. m in two coats for 1mm DFT

| PARAMETER              | TEST STANDARD USED                            | TYPICAL VALUES                                     |
|------------------------|-----------------------------------------------|----------------------------------------------------|
| Colour and Appearance  | Visual                                        | Smooth, satin finish                               |
| Packaging              | -                                             | 1 L, 4 L, 10 L, 20 L                               |
| Coverage               | -                                             | 120 - 140 sq.ft./liter/coat (depending on surface) |
| Drying Time            | Touch Dry: 30 - 45 mins / Recoat: 4 - 6 hours |                                                    |
| Water Repellency       | ISO 2323                                      | Excellent                                          |
| Lead & Mercury content | ASTMD 1210                                    | Nil                                                |

## 4. APPLICATION METHOD



### SURFACE PREPARATION

- Ensure the surface is clean, dry, and free from dust, grease, and loose particles.
- Fill cracks with suitable wall putty.
- Sand the surface smooth.



### PRIMING

- Apply one coat of high-quality Wall Primer.
- Allow to dry for 4 - 6 hours.
- Sand lightly before applying the topcoat.



### APPLICATION OF EMULSION

Thin the paint by mixing with clean water (30 - 40% by volume).  
Apply 2 - 3 coats of Duraguard Emulsion using a roller or brush.  
Ensure 4 - 6 hours drying time between coats.

## 5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for Duraguard Emulsion for detailed safety information.



Store in a cool, dry place away from direct sunlight.



Keep out of reach of children and away from foodstuff.



Wear protective eye and skin cover.



In case of eye contact, rinse with water and seek medical attention.



Do not dispose of waste into water courses.



Nil Lead & Mercury content.

### STORAGE PRECAUTIONS



Store at a cool, dry place at cool time.



### RECOMMENDED FOR



- ✓ Residential
- ✓ Commercial
- ✓ Exterior Walls
- ✓ Interior Walls

### HOW TO USE

- 1 Clean surface and loose particles.
- 2 Apply Primer
- 3 Apply Duraguard Emulsion



HIGH DURABILITY



WEATHER RESISTANT



EXCELLENT WASHABILITY



UV PROTECTION