

DURAGUARD

EXTERIOR WALL PRIMER

HEAVY-DUTY PRIMER FOR
MAXIMUM PROTECTION

DuraGuard Exterior is a high-performance exterior primer formulated to provide maximum protection against harsh weather conditions. It ensures excellent adhesion, uniform finish, and long-lasting durability for exterior surfaces.



MAXIMUM
PROTECTION

Protects surfaces from UV rays, rain, and pollution.



WEATHER
RESISTANT

Withstands extreme weather and climatic conditions.



COLOR
RETENTION

Enhances color life and keeps surfaces looking new.




ANTI-FUNGAL

Resists fungal growth and keeps exterior walls healthy.



AVAILABLE
PACK SIZES



1. WHY CHOOSE DURAGUARD EXTERIOR?



Maximum Protection

Provides a strong protective barrier against weather, UV rays, and pollutants.



Weather Resistant

Designed to perform in extreme heat, heavy rain, and humidity.



Color Retention

Enhances the true shade and extends the life of top coats.



Anti-fungal

Prevents fungal and algae growth for cleaner, healthier walls.

2. IDEAL FOR



Exterior Walls

Suitable for all types of exterior wall surfaces.



Facades

Ideal for building facades and outer elevations.



Boundary Walls

Protects boundary and compound walls.



Commercial Buildings

Perfect for commercial and industrial exteriors.

3. PRODUCT DETAILS

TECHNICAL INFORMATION

- Type

: Acrylic Primer
- Appearance

: Smooth, Viscous Liquid
- Colour

: White
- Solid Content

: 40 ± 2%
- pH

: 8.5 – 9.5
- Specific Gravity

: 1.30 – 1.50
- Drying Time (Touch Dry)

: 30 – 60 mins*
- Drying Time (Hard Dry)

: 3 – 4 hours*
- Recoating Time

: 4 – 6 hours*
- Coverage

: 10 – 12 sq.ft./kg/coat*
- Thinning

: Clean Water (up to 10%)
- Packaging

: 1Kg, 4Kg, 10Kg, 20Kg

* Results may vary depending on surface condition and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Adhesion Strength	≥ 1.5 MPa
Alkali Resistance	Excellent
Water Resistance	Excellent
Anti-fungal Property	Excellent
Stain Blocking	Good
Durability	Excellent
UV Resistance	Excellent
Flash Point	Non-Flammable

4. APPLICATION GUIDE



1. SURFACE PREPARATION
- Ensure the surface is clean, dry and free from dust, oil, grease, and loose particles.

• Remove any flaking paint, weak plaster or laitance.

• Repair cracks and level uneven areas.



2. PRIMER APPLICATION
- Stir DuraGuard Exterior Primer well before use.

• Apply one coat evenly using brush, roller or spray.

• Ensure uniform coverage.



3. RECOATING
- Allow to dry for 4 – 6 hours.

• Apply the top coat of your choice for best results.



4. TOP COAT APPLICATION
- Apply 2 coats of quality exterior paint.

• Follow recommended interval between coats.



5. CURING
- Allow the surface to cure for at least 7 days.

• Avoid heavy cleaning during the curing period.

5. SAFETY FEATURES & PRECAUTIONS



Refer to SDS for complete safety information.



Keep out of reach of children.



Wear protective gloves and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE



- Store in a cool, dry place.

• Keep containers tightly closed when not in use.

• Protect from direct sunlight and extreme heat.

• Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- ✓ Exterior Walls

✓ Facades

✓ Boundary Walls

✓ Commercial Buildings

TIPS FOR BEST RESULTS

- ★ Use a quality top coat for enhanced durability.

★ Ensure surface is completely dry before applying primer.

★ Do not paint in direct sunlight or on hot surfaces.

★ Stir well and do not over-thin the primer.

SCAN TO KNOW MORE



MAXIMUM PROTECTION



WEATHER RESISTANT



COLOR RETENTION



ANTI-FUNGAL

STRONG BASE. UNMATCHED PROTECTION.