

DURAGUARD INTERIOR WALL PRIMER

STRONG & UNIFORM ADHESION FOR THE PAINT FILM

Duraguard Interior is a high-performance interior wall primer that provides excellent adhesion, seals surfaces and ensures a smooth, long-lasting finish.



SUPERIOR ADHESION

Binds strongly to interior surfaces.



SMOOTH FINISH

Creates an even, professional base.



ENHANCED DURABILITY

Improves paint performance.



LOW ODOR

Interior friendly formula.



1. WHY CHOOSE DURAGUARD INTERIOR?



Strong Adhesion

Binds effectively to interior surfaces for a long-lasting paint finish.



Smooth & Even Finish

Creates a uniform surface for superior paint performance.



Enhances Durability

Increases the life and look of topcoat paint.



Low Odor Formula

User-friendly and safe for indoor application.

2. IDEAL FOR



Interior Walls

Living rooms, bedrooms, hallways.



Corridors

High-traffic passage areas.



Kitchens

Moisture-prone interior spaces.



High-Traffic Areas

Shops, offices, and commercial interiors.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Acrylic Primer
- Appearance : White / Milky
- Finish : Matt
- Specific Gravity : 1.40 – 1.50
- Drying Time : 1 – 2 hours
- Recoat Time : 3 – 4 hours
- Coverage : 10 – 12 m²/kg (per coat)

PERFORMANCE BENEFITS

- ✓ Superior adhesion
- ✓ Smooth and even base
- ✓ Enhances topcoat performance
- ✓ Long-lasting results

Note: Results may vary depending on substrate condition and application method.

4. APPLICATION GUIDE



SURFACE PREPARATION

- Clean the surface to remove dust, dirt, grease or loose particles.
- Ensure the surface is dry and free from moisture.



PRIMER APPLICATION

- Stir Duraguard Interior Primer well before use.
- Apply one coat evenly using a brush, roller or spray.
- Ensure uniform coverage.



DRYING TIME

- Allow 1–2 hours for drying.
- Apply the top coat once the primer is fully dry.



TOP COAT APPLICATION

- Use your preferred interior paint for the final finish.
- Follow the manufacturer's recommended drying time.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear gloves and mask during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and extreme heat.
- Shelf life: 12 months from date of manufacture.

RECOMMENDED FOR

- ✓ Interior & high-traffic walls
- ✓ Gypsum & plaster surfaces
- ✓ Cement & concrete surfaces
- ✓ AAC blocks & other masonry surfaces

HOW TO USE

- Clean the surface and remove dust, loose particles and contaminants.
- Apply primer evenly in one coat.
- Allow 1–2 hours to dry.
- Apply the top coat as per manufacturer's instructions.

SCAN TO KNOW MORE

