

EXTERIOR COATINGS

DURAGUARD PRO

(Premium Protective Coating)

A smooth water-based, modified acrylic exterior wall finish with silicon additives and Dust Proof Technology.

2
COATS



WATER BASED

LEAD FREE*
GUARANTEE

NO ADDED LEAD,
MERCURY OR
CHROMIUM

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



NEW MASONRY
PLASTER



HORIZONTAL
SURFACES
(LIKE LEDGES)



WINDOW TOPS



GENERAL
EXTERIOR WALLS

Ideal for a variety of exterior surfaces for long-lasting protection and beauty.

2. FEATURES AND BENEFITS

- ✓ Dust Proof Technology prevents micro-dust particles from settling
- ✓ Weather Guard withstands rainfall, humidity, and heat
- ✓ 6 Year Performance Warranty
- ✓ Excellent Anti-Fade protection against alkali and UV degradation
- ✓ Advanced Anti-Algal resistance prevents black spots
- ✓ Fantastic Shade Range 2100+ attractive shades
- ✓ Excellent Hiding power even in dark shades
- ✓ Best-in-class film integrity

3. PRODUCT DETAILS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Surface Dry Time	ASTM D1640	30 min
Sheen Levels	ASTM D523	4 – 7 at 60 deg GH
Drying Time (Recoat)	ASTM D1640	4 – 6 hours at 30°C
Thinning	ASTM D562	25 – 35% with Water
Application Viscosity (sec)	ASTM D1200	40
Storage Stability (thinned)	ASTM D1849	Use within 24 hours
Warranty	—	6 years



SHELF LIFE: 5 YEARS



COVERAGE: 55 – 65 sq.ft./ltr



FINISHES: Matt / Soft Sheen / Rich Sheen

4. APPLICATION METHOD



SURFACE PREPARATION

- New surfaces must be cured for at least 28 days and have a moisture content of less than 5 - 10%.
- Clean free of efflorescence, paint, dust, grease.
- Remove algae growth before application.
- Fill cracks up to 3mm with specialized filler.
- Address continuous seepage before top coating.



PRIMING

- Application of Wall Primer is mandatory.
- Allow primer to dry before topcoat.



APPLICATION

- Apply 2 coats of Duraguard Pro thinned with water (25-35%) with roller, brush or spray.
- Apply 3 coats on horizontal surfaces and for greater protection.
- Recoat after 4-6 hours.
- Consume thinned paint within 24 hours.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for handling details.



Store upright, in a cool, dry, well-ventilated place.



Keep away from children and animals.



Wear eye protection during application.



Wash skin contact with soap and water.



Do not pour paint down drains.



Dispose of drums responsibly.



No added Lead, Mercury or Chromium compounds.

RECOMMENDED FOR



- ✓ Exterior Masonry
- ✓ Painted Surfaces
- ✓ Concrete Surfaces
- ✓ Plaster Surfaces
- ✓ Ideal for Residential, Commercial & Institutional Buildings

HOW TO USE

- 1 Prepare surface
- 2 Apply Primer
- 3 Apply 2 coats of product



PREMIUM
PROTECTION



SILICON BOOST
TECHNOLOGY



DUST PROOF
TECHNOLOGY



WEATHER
GUARD



LONG LASTING
FINISH