

DURASHIELD EXT

**PREMIUM EXTERIOR EMULSION
WITH EXTENDED DURABILITY**

PREMIUM EXTENDED-DURABILITY FORMULA

Protect your home with Durashield Ext, the affordable exterior emulsion for a rich and lasting finish.

Powered by Twin Power Technology and Silicon Boost, this emulsion offers improved whiteness and superior coverage. Its modified acrylic binder ensures excellent film integrity, protecting walls against chalking, cracking, and peeling for years to come.



1. PERFECT FOR



**EXTERIOR
RESIDENTIAL
WALLS**



**EXTERIOR
COMMERCIAL
BUILDING SURFACES**



TWIN POWER AND SILICON BOOST

Advanced technology for better performance, durability and weather protection.



EXCELLENT CRACK AND PEEL RESISTANCE

Resists cracking and peeling to maintain a flawless finish for years.



ENHANCED FILM INTEGRITY AND MOISTURE PROTECTION

Superior binder strength protects walls from moisture, ensuring long-lasting beauty.



4-YEAR PERFORMANCE WARRANTY

Reliable performance backed by a 4-year warranty for complete peace of mind.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Acrylic Emulsion Based Paint

PHYSICAL PARAMETERS:

- Colour and appearance: White
- Packaging: 20 L
- Shelf life: 2 years
- Finish: Rich finish
- Application: Exterior walls
- Coverage: Varies with surface texture and porosity

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	Visual	Rich Finish
Colour	Visual	White
Solids by Volume	ASTM D 2697	45 – 55%
Specific Gravity	ASTM D 1475	1.25 – 1.40
pH	ASTM E 70	8.5 – 9.5
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Drying Time (Hard Dry)	ASTM D 1640	4 – 6 hours
Recoat Interval	–	4 – 6 hours
Application	–	Exterior walls
Coverage	–	120 – 140 sq.ft./L per coat*

*Coverage may vary depending on surface texture and porosity.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the exterior wall is clean, dry, and free from loose paint, dust, or grease before application.

>

2



PRIME THE WALL

Apply a suitable exterior primer to ensure optimal adhesion and long-term durability of the emulsion.

>

3



APPLY PAINT

Apply the required coats of Durashield Ext using a brush, roller, or spray, allowing adequate drying time between coats.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for Durashield Ext for detailed information about safety measures while handling the paint, which is available on request.



Store the container with the lid tightly closed, in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.



RECOMMENDED FOR



- ✓ Exterior residential walls
- ✓ Exterior commercial building surfaces

HOW TO USE

- 1 Prepare surface
- 2 Prime the wall
- 3 Apply required coats of Durashield Ext
- 4 Allow adequate drying time between coats.



**WATERPROOFING
LONG LASTING PROTECTION**



**UV RESISTANCE
PROTECTS FROM FADING**



**ANTI-ALGAL
KEEPS WALLS CLEAN**



**HIGH SCRUB RESISTANCE
TOUGH ON STAINS**