

EXTERIOR COATINGS

Durashield Emulsion

PREMIUM PROTECTIVE EXTERIOR PAINT

Weather-resistant latex paint providing high coverage and a smooth finish for beautiful exterior walls.



WATER BASED




LEAD FREE



NO ADDED LEAD, MERCURY OR CHROMIUM

WEATHER RESISTANT
SUPERIOR DURABILITY
EXCELLENT COVERAGE
SMOOTH FINISH

1. AREAS OF APPLICATION



NEW
MASONRY



OLD
PLASTER



RESIDENTIAL
BUILDINGS

Ideal for exterior surfaces that require long-lasting protection and an attractive, smooth finish.

2. FEATURES AND BENEFITS

- ✓ Latex technology for easy application and smooth finish
- ✓ Superior durability and enhanced appearance
- ✓ Excellent flow levelling and superior film integrity
- ✓ Economical value for beautiful exterior buildings
- ✓ Weather resistance against dust ingress and UV exposure
- ✓ High coverage: 35-45 Sq.ft./kg for 2 coats

3. PRODUCT DETAILS

PHYSICAL/CHEMICAL PARAMETERS

- Finish: Smooth Matt
- Packs Available: 20 kgs, 10 kgs, 5 kgs, 2 kgs
- VOC Content: Meets LEED criteria
- Safety: No added Lead, Mercury or Chromium compounds

Parameter	Typical Values
Curing Time for New Masonry	28 days
Surface Dry Time	30 minutes
Recoat Period (25°C, 50% RH)	4 - 6 hours
Shelf Life	3 years from manufacture

4. APPLICATION METHOD



SURFACE PREPARATION

Ensure surfaces are clean, dry, and free from loose paint, dust, grease, algae, and fungus.

Allow new masonry to cure for 28 days.

For old surfaces: damaged areas or surface irregularities should be repaired using epoxy-based mortar. All cracks larger than hairline shall be considered as moving and must be repaired with epoxy-based mortar.

All delaminated and splashed areas of concrete shall be repaired prior to application of PDD with epoxy-based mortar.



PRIMING & REPAIRS

For crack filling up to 3mm, use specialized Crack Seal.

Use Acrylic Wall Putty or 1:3 mix of white cement and sand for holes/dents.

Apply a generic Exterior Primer as recommended.



PAINT APPLICATION

Apply 2 coats of Latex Exterior Paint with a 4-6 hour recoat interval.

Dilution with water should be 35-45% by weight.

Apply first coat and then second coat using a brush or foam roller.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for detailed information



Store upright in a cool, dry place away from direct sunlight



Keep out of reach of children and away from foodstuffs



Wear eye protection during application



Do not breathe vapour or spray; wear nose pad during sanding



Do not pour leftover paint down the drain



Left-over paint/drums should be disposed of responsibly

STORAGE PRECAUTIONS



Store at cool and dry temperatures in tightly closed containers away from direct sunlight.



RECOMMENDED FOR



- ✓ New Masonry
- ✓ Old Plaster Surfaces
- ✓ Residential Buildings

HOW TO USE

- 1 Clean surface and remove loose particles.
- 2 Apply Primer.
- 3 Apply Durashield Emulsion.



WEATHER
RESISTANT



SUPERIOR
DURABILITY



EXCELLENT
COVERAGE



SMOOTH
FINISH