

DUSTGUARD EMULSION

**PREMIUM DUST-RESISTANT FORMULA
ADVANCED TECHNOLOGY FINISH**

DustGuard Emulsion is a high-performance exterior emulsion engineered with advanced Dust Proof Technology. It delivers 10% higher coverage, excellent UV protection, and a long-lasting ultra finish that keeps your exterior walls clean, vibrant, and protected for years.



**10% HIGHER
COVERAGE**



**EXCELLENT
UV PROTECTION**



**LOW VOC,
LEAD-FREE**



**GREEN BUILDING
COMPLIANT**

2. AREAS OF APPLICATION



EXTERIOR WALLS

FEATURES AND BENEFITS



10% HIGHER COVERAGE

Advanced formulation delivers 10% more coverage for greater efficiency and value.



DUST PROOF TECHNOLOGY

Special dust-repellent formula keeps surfaces cleaner for longer by resisting dust accumulation.



EXCELLENT UV PROTECTION

UV-resistant technology prevents shade fading and keeps your walls looking vibrant.



LOW VOC, LEAD-FREE

Environment-friendly, low VOC formula that is safe for your family and the environment.

3. PRODUCT DETAILS

Type: Exterior Emulsion Paint

Finish: Ultra Finish

Colour: As per shade card

Coverage: 10% higher coverage*

Packaging: 20 L

Shelf Life: 3 years

Application: Exterior walls

*Compared to standard emulsion paints.

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Ultra Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Coverage	ISO 11890-1	10% higher coverage*
Washability	IS 9845	Excellent
UV Resistance	QUV Accelerated Test	Excellent
VOC Content	As per BIS Standards	Low
Lead Content	ICP-OES	Below detectable limit
Application Method	—	Brush, Roller, Spray
Recommended Thinning	—	Up to 10% with clean water

4. APPLICATION METHOD



1. PREPARE SURFACE

Ensure the exterior surface is clean, dry, and free from loose particles, dirt, grease, or contaminants.



2. PRIME THE SURFACE

Apply a suitable primer to ensure optimal adhesion and long-term durability of the paint.



3. APPLY PAINT

Apply DustGuard Emulsion using a brush, roller, or spray. Allow sufficient drying time between coats.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the Safety Data Sheet (SDS) for detailed information on safe handling and usage.



Store the container with the lid tightly closed in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures. Protect from direct sunlight and frost.

RECOMMENDED FOR



- ✓ Residential Buildings
- ✓ Commercial Buildings
- ✓ Institutional Projects
- ✓ Hospitality Buildings

HOW TO USE

- 1 Clean the surface and remove dust, oil, or loose particles.
- 2 Apply the primer as per recommendation.
- 3 Let it dry for 4–6 hours before applying top coat.



**DUST
REPELLENT**



**EASY
CLEAN**



**ANTI-
FADING**



WASHABLE



**LONG LASTING
PERFORMANCE**



**LOW VOC,
LEAD-FREE**



**GREEN BUILDING
COMPLIANT**