

ECO ACRYLIC DISTEMPER

ECO-FRIENDLY DISTEMPER FOR INTERIOR WALLS

Eco Acrylic Distemper is an environmentally friendly, water-based distemper perfect for interior walls, delivering excellent coverage and a breathable finish for a healthy living space.



ECO-FRIENDLY



WATER-BASED



EXCELLENT
COVERAGE



BREATHABLE
FINISH



ECO-FRIENDLY

Low VOC, safe
for your home
and environment.



WATER-BASED

Easy to apply,
quick drying and
low odour.



EXCELLENT
COVERAGE

High hiding
power for a
uniform look.



BREATHABLE
FINISH

Allows walls to
breathe and
reduces dampness.

1. WHY CHOOSE ECO ACRYLIC DISTEMPER?



Eco-friendly

Formulated with low VOC & eco-safe ingredients, making it safe for your family and the environment.



Water-based

Easy to dilute with water, low odour and quick drying.



Excellent Coverage

High opacity and superior coverage ensures a smooth and uniform finish.



Breathable Finish

Allows moisture to escape, helping to prevent peeling and dampness.

2. IDEAL FOR



Interior Walls

Ideal for all types of interior masonry surfaces.



Ceilings

Provides a smooth, streak-free finish.



Low-traffic Areas

Perfect for areas with minimal wear and tear.



Residential Spaces

Designed for homes, apartments and living spaces.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Acrylic Distemper
- Finish : Matt
- Colour : As per shade card
- Viscosity : 90 – 110 KU @ 25°C
- Solids by Volume : 40 ± 2%
- Drying Time (Touch Dry) : 30 – 60 min
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 4 – 6 hrs
- Coverage : 80 – 100 sq.ft./litre/coat*
- No. of Coats : 2 – 3 Coats
- Thinner : Clean Water
- Packaging : 1L, 4L, 10L, 20L

* Coverage may vary depending on surface type, texture and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Appearance	Smooth, Uniform
Opacity	Excellent
Washability	Good
Water Resistance	Good
Alkali Resistance	Good
Fungus Resistance	Good
Flaking	No Flaking
VOC Content	Low VOC
pH Value	8.5 – 9.5
Coverage	80 – 100 sq.ft./litre /coat*

4. SURFACE PREPARATION & APPLICATION GUIDE



1. SURFACE PREPARATION

- Surface must be clean, dry and free from dust, dirt, grease, oil or loose paint.
- Scrape off flaking paint and sand the surface smooth.
- Fill cracks and holes with suitable putty and allow to dry.



2. PRIMING

- Apply suitable Acrylic Wall Primer for better adhesion and long lasting performance.
- Allow primer to dry completely.



3. DILUTION

- Dilute distemper with clean water.
- Normal dilution: 30 – 40% for first coat and 20 – 30% for subsequent coats.



4. APPLICATION

- Stir well before use.
- Apply 2 – 3 coats using a roller, brush or spray.
- Allow proper drying time between coats.



5. CLEANING

- Clean all tools and equipment with clean water immediately after use.

5. SAFETY FEATURES & PRECAUTIONS



Refer to SDS for complete safety information.



Keep out of reach of children.



Wear protective gloves and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, heat and moisture.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

- ✓ Interior Walls
- ✓ Ceilings
- ✓ Low-traffic Areas
- ✓ Residential Spaces

HOW TO USE

- Prepare the surface properly.
- Dilute as recommended and stir well.
- Apply 2 – 3 coats with proper drying time between coats.
- For best results, use with Colorsome Acrylic Wall Primer.

SCAN TO KNOW MORE

