



WATERPROOFING ELASTOSEAL

A Premium Elastomeric Waterproofing Coating



LEAD FREE



UV RESISTANT



WEATHER RESISTANT

1. AREAS OF APPLICATION



RETAINING WALLS



TERRACES



WET AREAS



PARAPET WALLS

Ideal for terraces, chajjas, wet areas, retaining walls, parapet walls and other exterior surfaces.

2. FEATURES AND BENEFITS

- ✓ High Flexibility
- ✓ Continuous Seamless Membrane
- ✓ Crack Bridging
- ✓ Good Weathering Resistance
- ✓ Resists Hydrostatic Water Pressure
- ✓ UV Resistant
- ✓ Easy to Apply by Brush or Roller

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Polyurethane Dispersion

PHYSICAL PARAMETERS:

- Colour: White
- Supply Condition: Viscous Liquid
- Solids by Weight: 60%
- Shelf Life: 2 Years
- Coverage: 1.5 – 2.0 kg per sq. m in two coats (for 1mm DFT)
- Pack Size: 20 L

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Weight Per Liter	ASTM D 1475	1.2 kg
Tensile Strength	ASTM D 2370	>1.5 MPa
Elongation	ASTM D 2370	450%
Crack Bridging Ability	AS-NZ 4548	Up to 4mm
Solid Content	ASTM C 1250	60%
Water Impermeability 7 MPa, 72 hours	BS EN 12390-8	0 mm
Colour of Dry Film	Visual	White

4. APPLICATION METHOD



SURFACE PREPARATION

- For new concrete, ensure curing curing (28 days, <10% moisture of mosth moisture). Mechanical sanding required.
- Use suitable Generic Acrylic Wall Putty.
- Old surfaces require repair with Generic Acrylic Repair Mortar and Generic Sanding Paper.
- For all surfaces, use a Generic Wall Primer.



PRIMING

- Apply a clean, clear coat of Generic Wall Primer.
- Re-apply on absorbent areas.
- Allow primer to surface dry for 2 – 3 hours.



APPLICATION OF ELASTOSEAL

- Mix well with a mechanical mixer.
- Apply the first coat at recommended coverage. Allow 8–10 hours to dry.
- Apply the second coat crosswise coverage.
- Wet test after at least 72 hours.

5. SAFETY FEATURES & PRECAUTIONS



Consult MSDS for detailed information.



Store tightly closed upright in cool dry place.



Keep out of reach of children and away from eatables.



In case of ingestion seek immediate medical attention.



Wear eye protection during application.



Wash hands thoroughly after use.



Contains no added Lead, down the drain or in water courses.

STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.




RECOMMENDED FOR




- ✓ New Consorvation
- ✓ Renovation
- ✓ Damp prone areas
- ✓ Before Top Cost Application

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 1 coat of Epery Primer evenly.
- 3 Let it dry for 4–6 hours before applying top coat.



HIGH FLEXIBILITY




WATERPROOF



CRACK BRIDGING



UV RESISTANT



SUPERIOR ADHESION



WEATHER RESISTANT