



Epoxishield

HIGH-PERFORMANCE EPOXY COATING

DOUBLE THE PROTECTION.
DOUBLE THE LIFE.

Epoxishield delivers heavy-duty epoxy protection that safeguards metal surfaces against rust, corrosion and harsh environmental conditions. Its superior adhesion and best-in-class coverage significantly extend the service life of steel and iron structures.

2X
RUST
PROTECTION

**SUPERIOR
METAL
LONGEVITY**

**BEST-IN-
CLASS
COVERAGE**

**HIGH WATER
& HUMIDITY
RESISTANCE**



WHY CHOOSE EPOXISHIELD?

2X Rust Protection
Advanced epoxy technology provides up to 2x better rust resistance compared to conventional coatings.

Superior Metal Longevity
A tough, durable barrier that extends the life of metal surfaces, reducing maintenance and repair costs.

Best-in-Class Coverage
Engineered for maximum spread and thickness control to deliver outstanding coverage and performance.

High Water & Humidity Resistance
Withstands harsh marine and atmospheric environments with excellent chemical resistance.

IDEAL FOR

Steel & Iron Substrates
Suitable for all ferrous metal surfaces.

Marine & Atmospheric Environments
Protects in saltwater, high humidity and corrosive conditions.

Commercial Construction Projects
Ideal for industrial structures, tanks, pipelines and more.

Residential & Non-Commercial Repairs
Perfect for metal fences, railings, roofs and other metal repairs.

TECHNICAL INFORMATION

Product Type
Two-Component Epoxy Coating

Finish
Gloss

Base
Epoxy Resin Based

Application
Steel, Iron & Mild Steel Surfaces

Coverage
Dry Film Thickness
75 – 100 microns per coat

Drying Time (25°C)
Surface Dry: 2 – 4 hours
Hard Dry: 12 – 16 hours*

Recoat Time
Min. 12 hours – Max. 7 days*

No. of Coats
2 Coats Recommended

Thinner
Epoxy Thinner

Shelf Life
24 months from date of manufacture

Available Packaging
250 ml, 500 ml, 1 L, 4 L, 20 L

KEY BENEFITS

2X Rust Protection

Superior Metal Longevity

Best-in-Class Coverage

High Water & Humidity Resistance

Corrosion Resistant

Chemical Resistant

High Durability

5-Year Performance Warranty

HOW TO APPLY

1 PREPARE SURFACE
Ensure the metal substrate is clean, dry, and free from loose rust, grease, oil or other contaminants. Abrasive blasting or wire brushing is recommended for

2 APPLY COATING
Mix the epoxy components thoroughly in the recommended ratio.

Apply evenly using a brush, roller or spray equipment to achieve uniform coverage.

3 ALLOW TO CURE
Allow the coating to dry and cure completely in a clean, well-ventilated area.

Full chemical and mechanical resistance develops after complete curing.

PROFESSIONAL TIP
For best performance, apply in dry conditions with temperature between 10°C and 40°C.

SAFETY FEATURES

Low Odor Formula

Non-Flammable (Post Application)

Tough & Impact Resistant

Safe for Professional Use

PRECAUTIONS

- Use in a well-ventilated area.
- Wear gloves, mask and eye protection during application.
- Avoid skin contact and inhalation of vapors.
- Keep away from children.
- Do not dispose of in drains or natural water bodies.

STORAGE PRECAUTIONS

- Store in a cool, dry place away from heat and direct sunlight.
- Keep container tightly closed when not in use.
- Do not store near food, beverages or animal feed.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

Industrial Structures

Storage Tanks & Pipelines

Bridges & Steel Frames

Factory Equipment

Railings, Fences & Gates

Metal Furniture & Fixtures

**2X RUST
PROTECTION**

SUPERIOR METAL LONGEVITY

**BEST-IN-CLASS
COVERAGE**

**HIGH WATER & HUMIDITY
RESISTANCE**

**5-YEAR
PERFORMANCE WARRANTY**