



INTERIOR WALL EMULSION

Extend Emulsion

Premium interior emulsion paint with a luxurious smooth finish.

- High Coverage
- Protective Shield
- Easy to Clean
- Long Lasting



WATER BASED
Low odor & fast drying

LEAD FREE* GUARANTEE
No added lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



Living Rooms



Bedrooms



Ceilings



Dry Internal Walls

Ideal for all interior walls and ceilings in residential, commercial, and institutional spaces.

2. FEATURES AND BENEFITS



SMOOTH, RICH FINISH

Delivers a luxurious smooth finish that enhances the look of your interiors.



EASY TO CLEAN & WASHABLE

Resists stains and allows easy cleaning for a fresh look.



LONG LASTING DURABILITY

Ensures long-term performance and color retention.



EXCELLENT HIDING & COVERAGE

High opacity provides excellent hiding power and uniform coverage.



ANTI-FUNGAL PROTECTION

Inhibits the growth of mold, mildew, and fungi on the painted surface.



FAST DRYING

Dries quickly to reduce waiting time between coats.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Dispersion Type: Acrylic Copolymer
- Finish: Ultra-Matte (< 3% at 85°)
- Pigment: High Grade Titanium Dioxide
- Sheen: White
- Pack Sizes: 20 L, 10 L, 4 L, 1 L
- Coverage: 1 – 2 kg per m² per coat*
- Recoat Time: 4 – 6 hours

*Coverage may vary depending on surface porosity, texture, and application method.

PHYSICAL PARAMETERS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Fineness of Dispersion	ASTM D 1210	<25 Microns
Volume Solids	ISO 3233	42% ± 2%
VOC Content	ISO 11890-2	<5 g/L
WFT (Wet Film Thickness)	Calculated	100 – 120 microns
DFT (Dry Film Thickness)	Calculated	42 – 50 microns
Heekertah Dispersion	ASTM D 2130	<5 g/L
VOC Comohication	ASTM D 2370	<5 g/L
Surface Dry Time	ASTM D 1250	30 Minutes
Surface Dry Time	Visual	30 Minutes

4. APPLICATION METHOD



SURFACE PREPARATION

- Surface must be clean, dry, and free from loose paint, dust, dirt, oil, grease, and other contaminants.
- Treat any surface imperfections with suitable wall primer and putty.
- Sand the surface smooth after putty application.
- Allow the surface to cure completely (minimum 28 days for new masonry).



PRIMING

- Apply one coat of suitable primer by brush or roller at the recommended coverage.
- Allow 4 – 6 hours for drying.
- Ensure proper adhesion and uniform priming before applying the top coat.



APPLICATION

- Stir the paint thoroughly before use.
- Apply two coats of Extend Emulsion using a brush, roller, or spray.
- Dilute with maximum 10% clean water if necessary.
- Allow 4 – 6 hours drying time between coats.
- Final cure is achieved after 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for comprehensive safety guidelines.



Keep out of reach of children.



Wear protective gloves, eye protection, and face mask.



In case of contact with eyes, rinse immediately with plenty of water.



Ensure adequate ventilation during application and drying.



Do not dispose of leftover paint in water courses.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep container tightly closed when not in use.
- Protect from direct sunlight and extreme heat.

RECOMMENDED FOR



New Construction



Renovation



Residential Interiors



Commercial Interiors

HOW TO USE

- Clean the surface and remove dust and loose particles.
- Apply 1 coat of suitable primer.
- Apply 2 coats of Extend Emulsion with proper interval.
- Enjoy a luxurious smooth finish.

