

Extraguard

PREMIUM PROTECTIVE FINISH

Advanced water-based emulsion crafted to deliver superior protection and extended coverage for a flawless, long-lasting exterior finish.

SUPERIOR WEATHER RESISTANCE

ANTI-FUNGAL SHIELD

ULTRA-DURABLE FORMULA


EASY-TO-CLEAN SURFACE



2. AREAS OF APPLICATION



EXTERIOR WALLS



OUTDOOR SURFACES

Ideal for exterior residential walls and general outdoor masonry surfaces.

FEATURES AND BENEFITS



10% HIGHER SURFACE COVERAGE

Provides up to 10% more coverage than standard economy paints for better efficiency and value.



SUPERIOR ANTI-CHALKING & ANTI-PEELING PROTECTION

Shields surfaces from chalking, cracking, and peeling for a beautiful, long-lasting finish.



ADVANCED WATER-RESISTANCE TECHNOLOGY

Delivers excellent resistance against rain, moisture, and harsh weather conditions.



INTEGRATED ANTI-ALGAL PROPERTIES

Protects walls from algae, fungus, and microbial growth for a cleaner and healthier exterior.

3. PRODUCT DETAILS

- Type : Emulsion Paint
- Finish : Premium Sheen
- Colour : As per shade card
- Packaging : 1 L, 4 L, 10 L, 20 L
- Shelf Life : 3 years
- Application : Exterior walls; Outdoor surfaces

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Premium Sheen Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Coverage	ISO 11890-1	Up to 10% more coverage*
Water Resistance	Internal Method	Excellent
Alkali Resistance	Internal Method	Excellent
Anti-Algal / Anti-Fungal	Internal Method	Effective
Application Method	—	Brush, Roller, Spray
Curing	—	No curing required

*Coverage may vary depending on surface texture, porosity and application method.

4. APPLICATION METHOD



1. PREPARE SURFACE

Ensure the exterior surface is clean, dry, and free from loose debris or dust.



2. APPLY PAINT

Apply the emulsion evenly using a high-quality brush, roller, or spray equipment.



3. FINISH

Allow the paint to dry thoroughly. No additional water curing is required.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the Safety Data Sheet (SDS) for detailed information on safe handling and usage.



Keep out of reach of children and away from eatables.



Do not pour leftover paint down the drain or in water courses.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Store the container with the lid tightly closed in a cool, dry place.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



In the event of spills, contain spillage using sand or earth.



No added lead, mercury or chromium compounds.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures. Protect from direct sunlight and frost.

RECOMMENDED FOR



- ✓ Residential Buildings
- ✓ Commercial Buildings
- ✓ Institutional Projects
- ✓ Renovation Projects

HOW TO USE

- 1 Clean the surface and remove dust, oil, or loose particles.
- 2 Apply the paint as per recommendation.
- 3 Let it dry completely before subjecting the surface to use.



10% MORE COVERAGE



SUPERIOR PROTECTION



ANTI-FUNGAL SHIELD



EASY TO CLEAN SURFACE