

FLEXGRIP PRO

High-Performance Tile Adhesive

STRONG BOND. FLEXIBLE BY DESIGN.

Flexgrip Pro is a premium, polymer-modified cementitious adhesive engineered for seamless tile-on-tile installations.

It delivers superior bonding strength and excellent grab while providing high flexibility and water resistance to accommodate thermal and physical movements with minimal shrinkage.



SUPERIOR
BONDING
STRENGTH



HIGH
FLEXIBILITY



WATER
RESISTANT



INTERIOR &
EXTERIOR
USE

2. AREAS OF APPLICATION



Tile-on-Tile
Installation



Fixing Tiles Over
Existing Floor Tiles



Fixing Tiles Over
Existing Wall Tiles

FEATURES AND BENEFITS



POLYMER-MODIFIED CEMENT FORMULATION

Advanced polymer-modified cement for enhanced performance and durability.



SUPERIOR BONDING & GRABBING STRENGTH

Ensures unbeatable adhesion and a strong, reliable grab for all types of tiles.



HIGHLY FLEXIBLE

Accommodates thermal and physical movements, preventing cracks and ensuring long-term performance.



EXCELLENT WATER RESISTANT PERFORMANCE

Protects against moisture and water penetration for a long-lasting bond.

3. PRODUCT DETAILS

DESCRIPTION:

Flexgrip Pro is a hassle-free, single-component tile adhesive designed specifically for tile-on-tile installations.

It provides excellent workability, high bond strength, and superior flexibility with minimal shrinkage, ensuring a durable and flawless finish.

TECHNICAL SPECIFICATIONS:

PARAMETER	DETAILS
Type	Polymer-modified cementitious tile adhesive
Application	Tile-on-tile installation; Fixing tiles over existing tiles on floors; Fixing tiles over existing tiles on walls
Form	Single component – powder
Colour	Grey
Water Requirement	As per mixing ratio
Open Time	Approx. 20 – 30 minutes
Adjustability Time	Approx. 20 minutes
Pot Life	Approx. 2 – 3 hours
Coverage	Approx. 3 – 5 kg/m ² (depending on tile size, surface and trowel notch)
Storage	Store in a cool, dry place. Protect from moisture.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the existing tile surface is clean, dry, and free from loose debris or contaminants.

2



MIX ADHESIVE

Blend the single-component powder with clean water until a smooth, lump-free consistency is achieved.

3



APPLY AND FIX

Spread the adhesive using a notched trowel and press the new tiles firmly into position.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for Flexgrip Pro which gives detailed information about safety measures while handling the material.



Store the container with the lid tightly closed in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store in a cool and dry place at ambient temperatures.

RECOMMENDED FOR



- ✓ Residential Buildings
- ✓ Commercial complexes
- ✓ Renovation projects
- ✓ New construction

HOW TO USE

- 1 Prepare surface as described.
- 2 Mix adhesive to required consistency.
- 3 Apply using notched trowel and fix tiles firmly. Allow 24 hours for trafficability.



STRONG &
RELIABLE BOND



HIGH FLEXIBILITY
PERFORMANCE



WATER
RESISTANT



MINIMAL
SHRINKAGE



FAST & EASY
APPLICATION