

FLEXIBOND EXT

ADVANCED FLEXIBLE WATERPROOF SEALANT

A high-performance, crack-bridging texture that enhances adhesion and creates a durable base for limitless design possibilities.



LOW VOC



ECO FRIENDLY



STRONG ADHESION

2. AREAS OF APPLICATION



Exterior Walls



Interior Surfaces



Protective Intermediary Layer



Base for Artistic Textures & Topcoats

FEATURES AND BENEFITS

- HIGH-PERFORMANCE CRACK-BRIDGING**
Effectively bridges fine cracks and masks surface undulations.
 - MODIFIED ACRYLIC WATER-BASED FORMULA**
Delivers strong adhesion and long-lasting performance.
- SUPERIOR ALL-WEATHER DURABILITY**
Engineered to withstand extreme weather conditions and moisture.
 - ENABLES UNIQUE ARTISTIC TEXTURES**
Creates a versatile base for distinctive texture patterns and decorative finishes.

3. PRODUCT DETAILS

CHEMICAL BASE:

Modified Acrylic
Water-Based Formula

PHYSICAL PROPERTIES:

- Color: Off White
- Packaging: Pouch
- Shelf Life: 2 years
- Coverage: 1.0 – 1.5 kg per sq. m (as per design & surface condition)

4. TECHNICAL SPECIFICATIONS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Appearance	—	Off White, Viscous Paste
Material Base	—	Modified Acrylic Water-Based
pH	ASTM E70	8.5 – 9.5
Specific Gravity	ASTM D1475	1.60 – 1.80
Drying Time (Surface Dry)	ASTM D1640	2 – 4 hours
Drying Time (Hard Dry)	ASTM D1640	24 – 48 hours
Application Temperature	—	10°C – 40°C
Coverage	—	1.0 – 1.5 kg per sq. m (as per design & surface condition)

5. APPLICATION METHOD



1. PREPARE SURFACE

Ensure the surface is clean, dry, and free from loose particles or contaminants.



2. APPLY BASE

Apply Flexibond Ext evenly to act as an intermediary layer for optimal adhesion.



3. TEXTURE AND FINISH

Create your desired texture pattern and allow the surface to dry before applying your chosen topcoat.

6. SAFETY FEATURES & PRECAUTIONS



Refer to the Safety Data Sheet (SDS) before use.



Keep out of reach of children and away from food & beverages.



Wear protective gloves and eye protection during application.



Ensure good ventilation during application and drying.



Do not dispose of in drains or water bodies.



In case of contact with eyes, rinse immediately with plenty of water and seek medical help.

7. STORAGE PRECAUTIONS



Store in a cool, dry place at temperatures between 5°C – 35°C.

- Keep the pouch tightly sealed when not in use.

8. RECOMMENDED FOR



- Exterior wall systems
- Interior surface finishes
- Protective intermediary layers
- Decorative texture applications

9. WHY CHOOSE FLEXIBOND EXT?

- Exceptional crack-bridging and adhesion
- Strong, durable, and weather-resistant
- Perfect base for artistic & decorative finishes
- Delivers long-lasting beauty and protection

10. SCAN TO KNOW MORE



WATERPROOF SEAL



HIGH FLEXIBILITY



WEATHER RESISTANT



STRONG ADHESION