

FlexiShield

HIGH-PERFORMANCE FLEXIBLE WATERPROOFING COATING

Protect your home with FlexiShield, the ultimate crack-bridging exterior emulsion powered by advanced PU Serum technology.

Engineered with a 100% acrylic water-based formula, FlexiShield offers superior 2.3x elongation to bridge hairline cracks effectively. Its specialized DPUR and anti-algal properties ensure your walls remain pristine, clean, and protected for up to 10 years.



-  **WATERPROOF**
LONG LASTING
PROTECTION
-  **2.3X SUPERIOR**
CRACK BRIDGING
RESISTS HAIRLINE CRACKS
-  **UV & WEATHER**
RESISTANT
ALL WEATHER PROTECTION
-  **ADVANCED**
ADHESION
STRONG BONDING POWER
-  **EASY TO APPLY**
SMOOTH FINISH
& DURABLE

1. AREAS OF APPLICATION



-  **EXTERIOR WALL SURFACES**
Ideal for all types of exterior wall surfaces including residential, commercial, and institutional buildings.
-  **SURFACES PRONE TO HAIRLINE CRACKS**
Specially formulated to bridge and prevent hairline cracks on exterior surfaces.

2. FEATURES AND BENEFITS

-  **ADVANCED PU SERUM TECHNOLOGY**
Integrated PU Serum enhances flexibility and performance for superior long-term protection.
-  **2.3X SUPERIOR CRACK BRIDGING**
Offers 2.3x higher elongation to bridge hairline cracks and prevent them from reappearing.
-  **UV & WEATHER RESISTANT**
Protects exterior walls from harsh UV rays, rain, and extreme weather conditions.
-  **10-YEAR PERFORMANCE WARRANTY**
Engineered for long-lasting durability and backed by a 10-year performance warranty*.
-  **DUST AND ALGAE-RESISTANT**
High-performance anti-algal and dust-repellent properties keep walls clean and beautiful.
-  **LOW VOC, ECO-FRIENDLY**
Low VOC, IGBC-compliant formulation for a healthier home and environment.

3. PRODUCT DETAILS

- Type** : Exterior Emulsion Paint
- Finish** : Rich Sheen / Luxurious Finish
- Colour** : As per Shade Card
- Packaging** : 1 L, 4 L, 10 L, 20 L
- Shelf Life** : 3 years from date of manufacture
- Application** : Exterior wall surfaces;
Surfaces with hairline cracks

4. TECHNICAL SPECIFICATIONS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Rich Sheen Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Elongation	Internal Method	2.3x Superior Elongation
Crack Bridging Ability	Internal Method	Excellent
Water Resistance	Internal Method	Excellent
Algal Resistance	Internal Method	Excellent
UV Resistance	Internal Method	Excellent
Coverage*	Internal Method	10 – 12 sq m/L/coat
Application Method	-	Brush, Roller, Spray
VOC Content	ISO 11890-1	Low (IGBC Compliant)

*Coverage may vary depending on surface texture and porosity.

5. HOW TO APPLY

-  **1. PREPARE SURFACE**
Ensure the exterior surface is clean, dry, and free from loose paint, dust, or contaminants.
-  **2. APPLY PRIMER**
Apply a coat of suitable exterior primer to ensure optimal adhesion and long-term protection.
-  **3. APPLY TOPCOAT**
Apply two coats of FlexiShield, allowing adequate drying time between coats for a luxurious, durable sheen.

6. SAFETY FEATURES & PRECAUTIONS

-  Read the Safety Data Sheet (SDS) carefully before use.
-  Store the container tightly closed in a cool, dry place away from direct sunlight and heat.
-  Keep out of reach of children and away from eatables.
-  May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
-  Do not pour leftover paint down the drain or in water courses.
-  In the event of spills, contain spillage using sand or earth.
-  Wear eye protection during application. In case of contact, rinse with copious amounts of water.
-  No added lead, mercury, or chromium compounds.

7. STORAGE PRECAUTIONS

-  Store in a cool and dry place at ambient temperatures. Protect from extreme heat, freezing, and direct sunlight.

8. RECOMMENDED FOR

-   Residential buildings
-  Commercial complexes
-  Institutional projects
-  Renovation projects

9. WHY CHOOSE FLEXISHIELD?

-  Advanced PU Serum technology
-  Superior crack bridging (2.3x elongation)
-  All-weather durability and protection
-  Keeps surfaces clean and vibrant
-  10-year performance warranty*

