

EMULSION

Fungiguard Emulsion

PREMIUM ANTI-FUNGAL & MOISTURE-RESISTANT FINISH

Fungiguard Emulsion delivers superior protection against mold, algae, and dampness while providing a smooth, durable and elegant finish to your walls.



ANTI-FUNGAL SHIELD
Advanced protection against mold and algae.



SUPERIOR HYDROPHOBICITY
Keeps walls dry by repelling water and moisture.

1. AREAS OF APPLICATION



INTERIOR WALLS



KITCHENS & BATHROOMS



EXTERIOR FAÇADES



MASONRY SURFACES

Ideal for areas exposed to moisture, humidity, and fungal growth.

2. FEATURES AND BENEFITS



ANTI-FUNGAL SHIELD
Advanced protection against mold and algae.



SUPERIOR HYDROPHOBICITY
Powerful water repellency to keep surfaces dry.



EASY-CLEAN TECHNOLOGY
Smooth finish for effortlessly wiping away stains.



BREATHABLE BARRIER
Allows moisture vapor to escape while blocking liquid water ingress.



DURABLE & LONG-LASTING
Excellent adhesion, washability and resistance to weathering.



LOW VOC & ENVIRONMENT FRIENDLY
Safe for indoor use and better for the environment.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- **Anti-Fungal Protection:**
Advanced Inhibitor Technology
- **Water Resistance:**
High Hydrophobic Emulsion

PHYSICAL PARAMETERS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish / Sheen	Visual	Smooth Matt
Weight per Liter	ISO 2811	~1.30 kg
Touch Dry Time	Internal Method	~30 Minutes
Recoat Time	Internal Method	4 - 6 Hours
Theoretical Coverage	Internal Method	10 - 12 sq. m/L/coat
VOC Content	EPA 24	<50 g/L
Water Vapor Permeability	ISO 7783	Class II

*Coverage may vary depending on surface porosity, texture, application method and color shade.

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure the surface is clean, dry, and free from dust, grease, and loose particles.
- Treat any existing fungal/mold growth with a suitable bio-wash solution.
- Remove all flaking or peeling paint and sand the surface to a smooth finish.
- Fill minor cracks and imperfections with an appropriate filler.
- Allow the surface to dry completely before painting.



PRIMING

- Apply one coat of Colorsome Water-Based Primer at the recommended coverage.
- Ensure the primer is compatible with the substrate and allow it to dry completely.
- For highly absorbent or porous surfaces, apply a second coat of Colorsome Water-Based Primer if required.
- Allow the primer to dry for 4–6 hours before applying the first coat of the finish.



APPLICATION

- Stir the paint thoroughly before use.
- Apply two coats using a high-quality synthetic roller or brush.
- Allow 4–6 hours drying time between coats.
- Coverage is dependent on surface porosity.
- For best results, avoid overthinning.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for comprehensive safety guidelines.



Ensure good ventilation during application and drying.



Keep out of reach of children.



Avoid contact with eyes and skin.



In case of eye contact, rinse immediately with plenty of water and seek medical advice.



Do not empty into drains or watercourses.



Dispose of container safely and responsibly.



STORAGE PRECAUTIONS

Store in a cool, dry, well-ventilated place. Keep container tightly closed when not in use.

Protect from direct sunlight and extreme heat.

RECOMMENDED FOR

- ✓ New & Previously Painted Surfaces
- ✓ Areas prone to high moisture
- ✓ Homes, Offices & Commercial Spaces



ANTI-FUNGAL SHIELD



SUPERIOR HYDROPHOBICITY



EASY-CLEAN TECHNOLOGY



BREATHABLE BARRIER