

GLOSSMATE

PREMIUM GLOSS ENAMEL PAINT

BRILLIANT SHINE. LASTING BEAUTY.

Glossmate Enamel Paint delivers a brilliant, high-gloss finish that resists yellowing and maintains its shine for years.



HIGH GLOSS
FINISH



SCRATCH
RESISTANT



EASY
CLEANING



WEATHER
RESISTANT



HIGH GLOSS FINISH

Delivers a brilliant, mirror-like shine that enhances any surface.



SCRATCH RESISTANT

Forms a tough, durable film that resists scratches and everyday wear.



EASY CLEANING

Smooth surface allows easy cleaning and maintenance.



WEATHER RESISTANT

Withstands harsh weather and UV rays without fading.

1. WHY CHOOSE GLOSSMATE?



Brilliant High Gloss

Provides a rich, mirror-like finish that adds elegance to every surface.



Scratch & Impact Resistant

Hard and durable film resists scratches, abrasions and minor impacts.



Easy to Clean

Smooth enamel surface repels dust and stains for effortless cleaning.



Weatherproof Protection

Resists moisture, UV rays and temperature changes for long life.

2. IDEAL FOR



Metal Surfaces

Gates, railings, grills, metal furniture, machinery.



Wood Work

Doors, windows, frames, panels.



Furniture

Tables, chairs, cabinets, shelves, wardrobes.



Doors & Windows

Main doors, shutters, window frames.

Ideal for both interior & exterior applications.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Alkyd Based Enamel Paint
- Finish : High Gloss
- Shade : As per shade card
- Viscosity : 80 – 90 KU @ 25°C
- Solid by Volume : 42 ± 2%
- Specific Gravity : 0.95 – 1.05 g/cc
- Drying Time (Touch Dry) : 2 – 3 hrs
- Drying Time (Hard Dry) : 6 – 8 hrs
- Recoat Time : 16 – 18 hrs
- Coverage : 12 – 14 m²/litre/coat*
- No. of Coats : 2 – 3 Coats
- Thinner : Enamel Thinner
- Packaging : 1L, 4L, 10L, 20L

* Coverage may vary depending on surface type, texture and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Gloss Level	90 – 95 GU @ 60°
Scratch Resistance	Excellent
Adhesion	Excellent
Flexibility	Good
Chemical Resistance	Good
Heat Resistance	Up to 70°C
Yellowing Resistance	Excellent
Weather Resistance	Excellent
Film Hardness	≥ H (Pencil)

4. SURFACE PREPARATION & APPLICATION GUIDE



1. SURFACE PREPARATION

- Surface must be clean, dry and free from dust, oil, grease, loose paint or rust.
- Smoothen rough areas with sandpaper.
- For metal, remove rust and apply suitable primer.



2. PRIMING

- Apply 1 coat of suitable primer for better adhesion and durability.
- Allow to dry for 16 – 18 hours.



3. THINNING

- Thin the paint using Enamel Thinner.
- Use 5 – 10% thinner for brush/roller application and 10 – 15% for spray.



4. APPLICATION

- Apply 2 – 3 coats using brush, roller or spray gun.
- Maintain proper interval of 16 – 18 hours between coats.
- Stir well before use.



5. CLEANING

- Clean all tools and equipment immediately after use with Enamel Thinner.
- Do not allow paint to dry on tools.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, mask and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, heat and moisture.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

- ✓ Metal Surfaces
- ✓ Wood Work
- ✓ Furniture
- ✓ Doors & Windows
- ✓ Interior & Exterior Use

HOW TO USE

- 1 Prepare the surface properly.
- 2 Apply suitable primer if required.
- 3 Apply 2 – 3 coats of Glossmate Enamel Paint.
- 4 Allow proper drying between coats for best results.



HIGH GLOSS FINISH



SCRATCH RESISTANT



EASY CLEANING



WEATHER RESISTANT



PREMIUM QUALITY