

GRAPHTECH SHIELD

Advanced Nano-Graphene Technology

Graphtech Shield is a next-gen exterior emulsion engineered with advanced Nano-Graphene Technology for unmatched protection and long-lasting beauty. It bridges cracks, resists harsh weather, algae, and fungus—keeping your walls strong and stunning for years.



IMPACT SHIELD



WATER REPELLENT



WEATHER DEFENSE




12-YEAR PROTECTION



2. AREAS OF APPLICATION



Exterior Masonry Walls



Crack-Prone Surfaces



Residential & Commercial Buildings



Boundary Walls & Facades

3. FEATURES AND BENEFITS

- 

ADVANCED GRAPHENE TECHNOLOGY
Enhances durability and provides superior protection against environmental stress.



CRACK BRIDGING UP TO 2MM
Effectively bridges hairline and minor cracks, preventing water ingress.



RESISTANT TO ALGAE & FUNGUS
Protects walls from algae, fungus, and microbial growth.
- 

12-YEAR PERFORMANCE WARRANTY
Assured long-term protection and peace of mind.



WATER REPELLENT
Forms a hydrophobic barrier that keeps walls dry and strong.



EXCELLENT WEATHER RESISTANCE
Withstands extreme weather conditions and UV exposure.

4. PRODUCT DETAILS

Type: Exterior Emulsion Paint
Finish: Rich Sheen
Colour: As per shade card
Packaging: 20 L
Shelf Life: 2 years
Coverage: 130 – 150 sq. ft./L/coat*

*Coverage may vary depending on surface texture and porosity.

PHYSICAL & PERFORMANCE PARAMETERS:

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Rich Sheen
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Crack Bridging Ability	ASTM C 836	Up to 2 mm
Algae & Fungus Resistance	Internal Method	No growth
Weather Resistance	ASTM G 154	Excellent
Water Absorption	ASTM C 67	Low
VOC Content	As per BIS Standards	Low
Flash Point	IS 101 (Part 1)	Non-flammable
Finish	—	Rich Sheen

4. APPLICATION METHOD

- 

1 PREPARE SURFACE
Ensure the exterior wall is clean, dry, and free from loose paint, dust, grease, or contaminants.



2 APPLY PRIMER
Apply a coat of suitable exterior primer to ensure optimal adhesion and surface uniformity.



3 APPLY TOPCOAT
Apply two coats of Graphtech Shield using a brush, roller, or spray for a durable, rich sheen finish.

6. SAFETY FEATURES & PRECAUTIONS

- 

Kindly refer to the MSDS for detailed information on safe handling and usage.



Store the container with the lid tightly closed in a cool, dry place.
- 

Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 

Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compounds.

7. STORAGE PRECAUTIONS

 Store in a cool and dry place at ambient temperatures. Protect from extreme heat, freezing, and direct sunlight.

8. RECOMMENDED FOR

- 
- Residential Buildings
 - Commercial Complexes
 - Institutional Projects
 - High Rainfall Zones
 - Before Top Coat Application

9. WHY CHOOSE GRAPHTECH SHIELD?

- Advanced Nano-Graphene Technology
- Superior crack bridging (up to 2mm)
- All-weather durability and protection
- Keeps surfaces clean and vibrant
- 12-year performance warranty

