

GuardMax Emulsion

Advanced Protective Emulsion
for Walls & Surfaces



WATER BASED

LEAD FREE*
GUARANTEE

SCRUB
RESISTANT

*All COLORSOME products
contain no added Lead, Mercury,
Arsenic or Chromium.

1. AREAS OF APPLICATION



INTERIOR
WALLS



CEILINGS



DRY AREAS



PRE-PRIMED
SURFACES

2. FEATURES AND BENEFITS

- ✓ Excellent Washability
- ✓ Long-term Durability
- ✓ Advanced Stainguard Technology
- ✓ Smooth Premium Finish
- ✓ Highly Durable Film
- ✓ Scrub Resistant
- ✓ Multisurface Application

3. PRODUCT DETAILS

PRODUCT PARAMETERS:

- Colour: White (Base)
- Packaging: 20 L Pail
- Shelf life: 2 Years

SPECIFICATIONS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Specific Gravity	ASTM D1475	1.3 ± 0.1 g/cc
Volume Solids	ASTM D2697	45 ± 2 %
Gloss Level (60°)	ASTM D523	Matt Finish < 10
Drying Time (Touch)	ASTM D5895	30 -60 Minutes
Recoat Time	ASTM D5895	4 -6 Hours

4. APPLICATION METHOD



SURFACE PREPARATION

- Clean surface from dirt, grease, loose paint.
- Sand existing paint to a matt finish.
- Fill cracks with suitable filler.
- Ensure surface is dry.



APPLICATION

- Apply over recommended Wall Primer.
- Apply 2 coats of GuardMax Emulsion by brush or roller.
- Allow 4-6 hours between coats.
- Use a roller for a uniform, premium finish.
- Clean tools with water immediately after use.

5. SAFETY FEATURES & PRECAUTIONS



Store the container tightly
closed in a cool, dry place.



Keep out of reach of children
and away from eatables.



May be harmful if swallowed.
Seek medical attention.



Wear eye protection during
application. In case of contact
with eyes, rinse immediately
with plenty of water and seek
medical advice.



May be harmful if swallowed.
Seek medical attention
immediately.



Do not pour leftover paint down
the drain or in water courses.



No added Lead, Mercury or
Chromium compounds.



This product contains no
intentionally added heavy metals.



STORAGE PRECAUTIONS

Store in a cool and dry place,
protected from direct sunlight
and extreme temperatures.



RECOMMENDED FOR

- ✓ Interior Decoration
- ✓ Residential Projects
- ✓ Commercial Spaces
- ✓ New & Repainting

HOW TO USE

- 1 Clean the surface and remove
dust and loose particles.
- 2 Apply 1 coat of **Epoxy** Primer
evenly.
- 3 Let it dry for 4-6 hours
before applying top coat.



ADVANCED
STAIN SHIELD



SMOOTH
PREMIUM FINISH



SCRUB
RESISTANT



MULTISURFACE
APPLICATION