

INTERIOR WALL FINISHES

Heritage Lime

LIME-BASED PAINT

Masterfully blending heritage elegance with modern sophistication, delivering a unique lime-based tactile finish that brings enduring beauty to your walls.



NATURAL
INGREDIENTS



LOW VOC
FORMULA



AREAS OF APPLICATION



CEMENT
PLASTER



CONCRETE



MASONRY



REPAINTING

ABOUT THE PRODUCT

Colorsome Heritage Lime is a premium lime-based interior paint crafted for spaces that value heritage, elegance and sophistication. Its artisanal matt finish with silicon tactility offers a soft, refined texture with exceptional durability and timeless appeal.

FINISH
Matt
(≤ 5 at 60°)

FLASH POINT
Not applicable

STABILITY
Use within
24 hours

NO ADDED
Lead, Mercury,
Arsenic or
Chromium

FEATURES & BENEFITS



LIME-BASED COMPOSITION
Celebrates sustainability and heritage.



SUPERIOR DURABILITY
Silicon tactility offers superior durability and lasting resilience.



100+ HERITAGE SHADES
100+ heritage-inspired shades for timeless luxury.



ARTISANAL MATT FINISH
Delivers rich, refined, textured surfaces.



LOW VOC FORMULATION
Low VOC formulation makes luxury conscientious.



STAIN RESISTANT & EASY TO CLEAN
Unmatched resistance against 14 common household stains.

TECHNICAL INFORMATION

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Specific Gravity	IS101 Part 1 Sec 1	1.38 – 1.42
Drying Time (Surface Dry)	IS101 Part 3 Sec 1	30 Minutes
Recoat Time	-	4 – 6 Hours
Washability	-	Best in Class
Shelf Life	-	36 Months
Coverage	-	100 – 120 Sq.ft / Ltr / Coat (approx.)
Available Packs	-	1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr
Warranty	-	10 Year Warranty*

*Terms and conditions apply. Please refer to Colorsome Warranty Guide.

RECOMMENDED USES



Ideal for interiors of homes, offices, hotels, commercial spaces and premium architectural projects.



Enhances walls with a graceful lime-based matt texture.



Suitable for new as well as repainted surfaces.



Perfect for spaces that demand sophistication, sustainability and long-lasting beauty.

APPLICATION GUIDE (STEP-BY-STEP)

1

SURFACE PREPARATION



- Sand the surface with Sanding Paper 180 to remove loose particles, paint, dust, grease or contamination.
- Wipe clean.

2

PRIMING



- Apply a coat of suitable Wall Primer and allow to dry for 4-6 hours.
- For putty surfaces, smoothen with 2 coats of Acrylic Wall Putty, allowing 4-6 hours between coats.

3

MIXING



- Thin 1 liter with 300 – 350 ml of clean water.
- Stir well and strain before use.

4

APPLICATION



- Apply 2 coats with 4-6 hours gap using a Short Nap roller followed by foam roller.
- An extra coat may be required for complete hiding.

5

RECOATING



- Allow 4-6 hours drying time between coats for best results.

SAFETY FEATURES & PRECAUTIONS



Do not apply below 10°C or if temperature may drop to this level within 4 hours.



Do not over-thin or over-extend the brush.



Tint using authorized machine colourants only.



Stir well and strain before use. Tinted paints need thorough shaking before use.



Do not apply to surfaces in permanent contact with water.



Store container tightly closed in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. Wear eye protection and suitable nose pad during application.



May be harmful if swallowed. Wear from eatables.



In case of contact with eyes, rinse with water and seek medical advice.



Do not breathe vapour or spray. Do not pour leftover paint down the drain.



In the event of spills, contain using sand or earth. Refer to MSDS for detailed safety information.

AVAILABLE PACKS



HERITAGE
INSPIRED



NATURAL
LIME BASED



BREATHABLE
SURFACES



DURABLE &
LONG LASTING



LUXURY
MATTE FINISH

BEAUTIFUL SPACES.
TIMELESS HERITAGE.