

TILE ADHESIVE FOR STONE & HEAVY TILE

High-performance, cement-based polymer modified adhesive for heavy tiles, granites, marbles and natural stones



-  **WATER RESISTANT**
-  **TRAFFICABLE (24H)**
-  **HIGH BOND STRENGTH**

1. AREAS OF APPLICATION



Interior Wall & Exterior Wall



Interior Floor & Exterior Floor



Concrete Slabs



Cement-based Screed

Ideal for heavy duty tiling on interior/exterior walls and floors, concrete slabs, cement screeds and other cementitious substrates.

2. FEATURES & BENEFITS

- ✓ Meets specifications of IS 15477:2019 Type 1T and ISO 13007-1:2014 C2TE.
- ✓ Excellent adhesion with stones and heavy tiles.
- ✓ Long pot life & extended open time simplifies installation.
- ✓ Slip resistant for horizontal and vertical application.
- ✓ Single component, ready-to-use with special additives for ease of application.
- ✓ Ready for traffic after 24 hours of fixing.
- ✓ Convenient – no hacking required on vertical concrete.
- ✓ Saves time – no pre-soaking of tiles or water curing needed.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Cement-based polymer modified single-component powder.

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Physical Appearance	Visual	Free flowing powder, grey
Pack Sizes	-	20 Kgs, 30 Kgs
Shelf Life	-	1 Year from manufacture
Mixing Ratio	-	23-25% with water
Minimum Bed Thickness	-	6-8 mm
Coverage	For 6mm bed thickness	1 – 1.25 Sq. Ft/ Kg

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure surface is sound, clean, dry and free of contamination.
- Repair uneven surfaces.
- Poor or uneven surfaces should be repaired and level finished.
- Wash floor/wall 2-3 hours before application for Saturated Surface Dry (SSD) condition.
- Clean tile surfaces.



MIXING

- Take water in clean bucket and add adhesive powder.
- Mix continuously with mechanical mixer to get a smooth lump-free paste.
- Stand for 5 minutes.
- Remix before use.



APPLICATION PROCEDURE

- Apply 6-8 mm bed on substrate and back of stone/tile with 12 mm notched trowel.
- Fix ensuring 100% contact, hammering gently with soft mallet.
- Leave adequate joints using spacers.

5. SAFETY FEATURES & PRECAUTIONS



Store bag tightly closed in a cool, dry place.



Keep out of reach of children and away from eatables.



Wear eye protection and a suitable nose pad.



In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Don't fix tiles in extreme low temperatures. Mechanical support needed for heavy tiles.

PACK SIZES



20 Kgs



30 Kgs

RECOMMENDED FOR



- ✓ Interior/Exterior Walls
- ✓ Interior/Exterior Floors
- ✓ Large Stone/Tile

USAGE GUIDELINES

- ✓ Always mix powder in water
- ✓ Surface should be sound and SSD
- ✓ Apply on substrate and tiles

