

WATERPROOFING

HydroFlex

Premium Elastomeric Waterproofing Membrane



WATER BASED



LEAD FREE*
GUARANTEE



UV
RESISTANT

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium compounds.

1. AREAS OF APPLICATION



EXTERIOR WALLS



TERRACE



WET AREAS



PARAPET WALLS

Ideal for exterior walls, terrace, wet areas, parapet walls and other exterior horizontal and vertical masonry surfaces.

2. FEATURES AND BENEFITS

- ✓ 10Y Extreme Durability
- ✓ Excellent resistance to weathering
- ✓ Extreme UV Resistant
- ✓ Elastic property bridges minor cracks
- ✓ Flexible Crack Bridging
- ✓ Safe, non-toxic formulation
- ✓ Water-Based for ease of use
- ✓ No added heavy metals

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Polyurethane Dispersion

PHYSICAL PARAMETERS:

- Colour and appearance: White (viscous paste)
- Packaging: 20 L
- Shelf life: 2 Years
- Coverage: 1.5 - 2 kg per sq. m in two coats for 1mm DFT

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Color and appearance	—	White (viscous paste)
Packaging	—	20 L
Shelf life	—	2 Years
Coverage	—	1.5 - 2 kg per sq. m in two coats
Tensile Strength	ASTM D 2370	>1.5 MPa
Crack Bridging Ability	AS-NZ 4548	Up to 4mm
Water impermeability	BS EN 12390 - 8	0 mm

4. APPLICATION METHOD



SURFACE PREPARATION

e.g. Clean the surface with wire brush and remove dust and loose particles. For major cracks, use suitable acrylic putty.

Old Concrete Flexer: damaged areas or surface irregularities should be repaired using epoxy-based mortar. All cracks larger than hairline shall be considered as moving and must be repaired with epoxy-based mortar.

All delaminated and splashed areas of concrete shall be repaired prior to application of PUD with excised mortar.



PRIMING

Apply a uniform coat of Water Primer.



APPLICATION

Apply two coats of HydroFlex at recommended coverage. Ensure sufficient drying time between coats.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for detailed information.



Keep out of reach of children.



Wear eye protection.



Damp prone areas.



In case of contact with eyes, rinse with water.



Do not breathe vapour or spray.



Store in a cool, dry place.

STORAGE PRECAUTIONS



Store in a cool, dry place.



RECOMMENDED FOR



- ✓ New Construction
- ✓ Renovation
- ✓ Damp prone areas
- ✓ Before Top Coat Application

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 1-coat of Epery Primer evenly.
- 3 Let it dry for 4-6 hours before applying top coat.



WATERPROOF



CRACK BRIDGING



UV RESISTANT



WEATHER RESISTANT