

WATERPROOFING HYDROSHIELD PRO

Advanced waterproofing coating for exterior horizontal and vertical masonry surfaces.



WATER BASED



LEAD FREE*
GUARANTEE



UV
RESISTANT

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



TERRACES



PARAPET
WALLS



NEW
MASONRY



CHAJJAS

Ideal for terraces, parapet walls, new masonry, chajjas and other exterior horizontal and vertical surfaces.

2. FEATURES AND BENEFITS

- ✓ Superior waterproofing (5 bar horizontal / 3 bar vertical positive pressure)
- ✓ Crack bridging ability up to 0.5mm on horizontal surfaces
- ✓ Best in class flexibility with 150% elongation
- ✓ 5 Years Adhesion Warranty
- ✓ Single product for vertical and horizontal applications
- ✓ Superior adhesion to all masonry and cementitious surfaces
- ✓ Reduces surface temperature up to 10°C
- ✓ Applicable on high moisture surfaces (up to 70%)

3. PRODUCT DETAILS

PHYSICAL PARAMETERS:

- Shelf life: 5 years from date of manufacture
- Colors available: White
- Coverage (Horizontal): 15 sq.ft/ltr (3 coats)
- Coverage (Vertical): 45 sq.ft/ltr (Self-priming + Undiluted coat)
- Packs available: 1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr

TEST & PHYSICAL PROPERTIES

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Adhesion Strength	ASTM D 4541	Minimum 1.5 MPa
Tensile Strength (14 days)	ASTM D 2370/98	1.5 ± 0.15 MPa
% Elongation (14 days)	ASTM D 2370/98	380 ± 10% (Horizontal)
Crack Bridging (14 days)	AS/NZ 4548	3.5 ± 0.35 mm (Horizontal)
Water Vapour Permeability	EN ISO 7783	4.1 g/m ² /day
% Solids	ASTM C 1250	54 - 60% @ 120°C/1 hr
Weight per Liter	IS 101	1.19 - 1.32 @ 30°C

4. APPLICATION METHOD



1 SURFACE PREPARATION

New masonry cures should be cured for 28 days and have moisture content of less than 5%. Excessive laitance, dust, and debris should be removed mechanically, ensuring proper drainage. Clean using loose paint, dust, or grease using wire brushing or water jet.



2 PRIMING

Apply one self-priming coat of HydroShield Pro (diluted with water in 3:1 ratio by volume) at 55 sq. ft./ltr. Allow primer to dry completely.



3 APPLICATION

Two subsequent coats are applied on both vertical and horizontal surfaces as detailed in the text. Ensure that a continuous blanket over the roof – continuous continuous blanket over the roof and parapet.

5. SAFETY FEATURES & PRECAUTIONS

-  Refer to MSDS for detailed information.
-  Store in a cool, dry place with lid tightly closed.
-  Keep out of reach of children and away from eatables.
-  Wear eye protection during application.
-  Wash skin with soap and plenty of water upon contact.
-  Do not pour paint down drains, contain spills with sand.
-  No added Lead, Mercury or Arsenic or Chromium compounds.

STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.



RECOMMENDED FOR



- ✓ Terraces
- ✓ Parapet Walls
- ✓ New Masonry
- ✓ Chajjas

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 1-coat of HydroShield Pro (self-primer) as per dilution.
- 3 Let it dry for 4–6 hours before applying next coat.



WATERPROOF



CRACK BRIDGING



UV RESISTANT



WEATHER RESISTANT