

UNDERCOATS

HYDROSHIELD WALL PUTTY

Premium White Cement-Based Wall Putty with Advanced Silicone Technology for Smooth, Durable Interior & Exterior Surfaces.



WATER BASED



LEAD FREE* GUARANTEE



1. AREAS OF APPLICATION




NEW
PLASTERED
WALLS



INTERIOR
WALLS



EXTERIOR
WALLS



CONCRETE
SURFACES



CEILING
SURFACES

Ideal for interior and exterior walls, ceilings, concrete surfaces and other masonry substrates.

2. FEATURES & BENEFITS

- ✓ Superior Water Resistance
- ✓ Crack Resistant Finish
- ✓ Smooth & Creamy Application
- ✓ High Coverage
- ✓ Excellent Adhesion
- ✓ Bright White Finish
- ✓ Strong Intercoat Bonding
- ✓ Low Shrinkage
- ✓ No Water Curing Required

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- White Cement
- Fine Mineral Fillers
- Polymer Modifiers
- Silicone Additives

PHYSICAL PARAMETERS:

PARAMETER	TYPICAL VALUE
Appearance	Fine White Powder
Colour	White
Coverage	1 – 1.5 sq.m/kg @1mm
Pot Life	45 Minutes
Surface Dry	30 Minutes
Recoat	6 – 8 Hours
Shelf Life	12 Months
Pack Sizes	1kg, 5kg, 20kg, 30kg, 40kg



4. APPLICATION METHOD



SURFACE PREPARATION

- Cure new plaster for 28 days.
- Remove dust, grease and loose particles.
- Repair cracks before application.
- Ensure dry, sound substrate.



MIXING

- Add clean water gradually.
- Mix until smooth lump-free paste.
- Allow standing for 5 minutes.
- Remix before use.



APPLICATION

- Apply first coat using putty knife.
- Allow 6 – 8 hours drying.
- Apply second coat.
- Light sanding after complete drying.

5. SAFETY FEATURES & PRECAUTIONS



Wear gloves and safety goggles



Avoid inhaling dust



Keep away from children



Store in cool, dry place



Dispose waste responsibly



Refer MSDS before use

PACKAGING SIZES



RECOMMENDED FOR

- ✓ Interior Walls
- ✓ Exterior Walls
- ✓ New Plaster
- ✓ Concrete Surfaces
- ✓ Ceiling Repairs
- ✓ Renovation

HOW TO USE

- 1 Prepare Surface
- 2 Mix with Water
- 3 Apply 1st Coat
- 4 Apply 2nd Coat
- 5 Sand Smooth

