

JET EMULSION

SUPER PREMIUM INTERIOR PAINT

ELEGANT FINISH. LASTING IMPRESSION.

Jet Emulsion is a super premium interior paint that delivers an unmatched hide, velvet-smooth finish and long-lasting beauty to your walls.

- 

SMOOTH FINISH
- 

WASHABLE
- 

LOW VOC
- 

EASY APPLICATION



- 

SMOOTH FINISH

Delivers a rich, velvet-smooth finish that enhances the beauty of your interiors.
- 

WASHABLE

Resists stains and allows easy cleaning without affecting the paint finish.
- 

COLOR RETENTION

Advanced formulation ensures long-lasting color brilliance and freshness.
- 

LOW VOC

Low Volatile Organic Compounds for a healthier indoor environment.

1. WHY CHOOSE JET EMULSION?

- 

Velvet-Smooth Finish

Provides a fine, even and luxurious finish that elevates your interiors.
- 

Highly Washable

Superior washability ensures easy removal of stains, keeping walls looking new for years.
- 

Long-Lasting Colors

Advanced pigments deliver excellent color retention and resist fading.
- 

Low VOC & Odor

Low VOC content ensures minimal odour and a healthier living space for you and your family.

2. IDEAL FOR

- 

Living Rooms

Adds elegance and warmth to your living spaces.
- 

Bedrooms

Creates a calm and relaxing atmosphere.
- 

Offices

Enhances productivity with soothing and refreshing walls.
- 

Hotels

Delivers a premium look with long-lasting appeal.

Suitable for new construction and repainting projects.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Acrylic Emulsion Paint
- Finish : Smooth Matt
- Colour : As per shade card
- Viscosity : 90 – 110 KU @ 25°C
- Solid by Volume : 40 ± 2%
- Specific Gravity : 1.30 ± 0.05
- Drying Time (Touch Dry) : 30 – 45 mins
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 4 – 6 hrs
- Coverage : 12 – 14 m²/litre/coat*
- No. of Coats : 2 Coats
- Thinner : Clean Water
- Packaging : 1L, 4L, 10L, 20L

* Coverage may vary depending on surface type, texture and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Opacity (Hiding Power)	Excellent
Washability	Excellent
Scrub Resistance	Excellent
Colour Retention	Excellent
Stain Resistance	Excellent
Fungus Resistance	Excellent
Alkali Resistance	Excellent
Chalking Resistance	Excellent
Low VOC	Yes
Coverage	12 – 14 m²/litre

4. SURFACE PREPARATION & APPLICATION GUIDE

- 

1. SURFACE PREPARATION

 - Surface must be clean, dry and free from dust, oil, grease, loose paint or rust.
 - Remove any peeling or flaking paint.
 - Repair cracks and holes with suitable filler and allow to dry.
- 

2. PRIMING

 - Apply 1 coat of Uniprime Interior Wall Primer for best results.
 - Allow to dry for 4 – 6 hours.
- 

3. THINNING

 - Thin with clean water up to 10 – 15% (by volume).
 - Stir well before use.
- 

4. APPLICATION

 - Apply 2 coats using brush, roller or spray gun.
 - Maintain proper interval of 4 – 6 hours between coats.
- 

5. CLEANING

 - Clean all tools and equipment with water immediately after use.
 - Do not allow paint to dry on tools.

5. SAFETY FEATURES & PRECAUTIONS

- 

Refer to MSDS for complete safety information.
- 

Keep out of reach of children.
- 

Wear protective gloves, mask and goggles during application.
- 

In case of contact with eyes, rinse immediately with plenty of water.
- 

If swallowed, seek medical advice immediately.
- 

Ensure adequate ventilation during application and drying.
- 

Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS

- 
- Store in a cool, dry place.
 - Keep containers tightly closed when not in use.
 - Protect from direct sunlight, heat and moisture.
 - Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

- ✓ Living Rooms
- ✓ Bedrooms
- ✓ Offices
- ✓ Hotels
- ✓ New Construction
- ✓ Repainting Projects

HOW TO USE

- 1 Prepare the surface properly.
- 2 Apply Uniprime Interior Wall Primer.
- 3 Apply 2 coats of Jet Emulsion.
- 4 Allow proper drying between coats for best results.

