

Lithos Ext

PREMIUM EXTERIOR TEXTURE FINISH
ULTRA-DURABLE & FLEXIBLE

Transform your exterior walls with the authentic, enduring elegance of **natural stone aesthetics**.

Lithos Ext combines striking stone-inspired designs with superior weather protection for a lasting finish. Its advanced formula ensures excellent film integrity and moisture resistance, backed by a 10-year performance warranty.



AUTHENTIC
STONE-INSPIRED
TEXTURES



SUPERIOR
ALL-WEATHER
RESISTANCE



HIGH-INTEGRITY
MOISTURE
PROTECTION



10-YEAR
PERFORMANCE
WARRANTY

1. AREAS OF APPLICATION



Exterior Walls

2. FEATURES AND BENEFITS



AUTHENTIC
STONE-INSPIRED
TEXTURES

Distinct stone design
(Granite, Sand, Flakes,
and Sparkle) for a
natural, premium look.



SUPERIOR
ALL-WEATHER
RESISTANCE

Engineered to withstand
harsh weather
conditions and UV
exposure.



HIGH-INTEGRITY
MOISTURE
PROTECTION

Provides excellent film
integrity and long-lasting
protection against
moisture penetration.



10-YEAR
PERFORMANCE
WARRANTY

Backed by a 10-year
warranty for worry-free,
long-term performance
and durability.

3. PRODUCT DETAILS

COMPOSITION

Premium blend of high-quality aggregates, resins, additives, and pigments.

PHYSICAL PROPERTIES

- Finish: Distinct stone design (Granite, Sand, Flakes, and Sparkle)
- Packaging: 20 L
- Shelf Life: 2 years
- Application: Exterior walls
- Drying Time: Touch dry in 4 – 6 hours*
- Colours: Available in a wide range of shades

TECHNICAL SPECIFICATIONS

PARAMETER	DETAILS
Application	Exterior walls
Binder Type	Acrylic Modified Emulsion
Drying Time	Touch dry in 4 – 6 hours*
Recoating Time	After 24 hours
Theoretical Coverage	1.5 – 2.0 kg per sq. m.**
No. of Coats	2 coats recommended
Finish	Distinct stone design (Granite, Sand, Flakes, and Sparkle)
Shelf Life	2 years from date of manufacture in original sealed container
Storage	Store in a cool, dry place. Protect from direct sunlight and frost.

*Under standard application conditions.

**Coverage may vary depending on surface texture, porosity and application method.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the wall surface is clean, dry, and free from loose debris or contaminants.

2



APPLY PRIMER

Apply a compatible primer to ensure optimal adhesion and a uniform base for the texture.

3



APPLY TEXTURE

Evenly apply the chosen stone finish using professional tools to achieve the desired aesthetic effect.

5. SAFETY FEATURES & PRECAUTIONS



Read the product label
and technical data
sheet before use.



Wear appropriate
gloves and protective
clothing during
application.



Keep out of reach
of children and
away from food
and feed.



Avoid contact
with eyes. In case
of contact, rinse
thoroughly with
water and seek
medical advice.



Do not pour leftover
material down the
drain or in water
courses.



In case of spills,
contain spillage
using sand or
earth.

6. STORAGE PRECAUTIONS



Store in a cool, dry place
at ambinal temperatures.
Keep the container tightly
closed when not in use.

7. RECOMMENDED FOR



- ✓ Residential Building Facades
- ✓ Commercial Establishments
- ✓ Renovation Projects
- ✓ Decorative Exterior Walls

8. HOW TO USE

- 1 Clean the surface and remove dust, grease, and loose particles.
- 2 Apply a suitable primer/base coat.
- 3 Evenly apply the Lithos Ext texture using professional tools.

SCAN TO KNOW MORE



SCRUB
RESISTANCE



FLEXIBLE
MEMBRANE



ADVANCED
COLOR



SUN
PROTECTION