

LithoTex

PREMIUM ARCHITECTURAL FINISH

Transform your exterior walls with the enduring, natural aesthetic of **LithoTex** stone-composite texture. A sophisticated finish with superior protection and a complex surface feel.



DURABLE
STONE-COMPOSITE
FORMULATION



EXCELLENT
WEATHER &
MOISTURE
RESISTANCE



SOPHISTICATED
NATURAL STONE-
INSPIRED
AESTHETIC



10-YEAR
PERFORMANCE
WARRANTY

1. AREAS OF APPLICATION



Exterior Residential Walls



Commercial Building Facades

2. FEATURES AND BENEFITS



DURABLE STONE-COMPOSITE FORMULATION

Made with crushed stone, sand, and gravel for a long-lasting textured finish.



EXCELLENT WEATHER & MOISTURE RESISTANCE

Superior film integrity protects walls from harsh weather and moisture penetration.



SOPHISTICATED NATURAL STONE- INSPIRED AESTHETIC

Delivers a complex surface feel and sight with a natural, premium look.



10-YEAR PERFORMANCE WARRANTY

Backed by a 10-year warranty for lasting performance and peace of mind.

3. PRODUCT DETAILS

COMPOSITION

Crushed Stone, Sand, Gravel & Acrylic Modified Emulsion

PHYSICAL PROPERTIES

- **Finish:** Aesthetic finish with complex surface feel and sight
- **Packaging:** 20 L
- **Shelf Life:** 2 years
- **Application:** Exterior walls
- **Drying Time:** Does not require curing
- **Colours:** Available in a wide range of shades

TECHNICAL SPECIFICATIONS

PARAMETER	DETAILS
Application	Exterior walls
Binder Type	Acrylic Modified Emulsion
Thinner	Water (as per requirement)
Drying Time	Does not require curing
Recoating Time	4 – 6 hours
Theoretical Coverage	1.5 – 2.0 kg per sq. m.**
No. of Coats	2 coats recommended
Finish	Aesthetic finish with complex surface feel and sight
Shelf Life	2 years from date of manufacture in original sealed container
Storage	Store in a cool, dry place. Protect from direct sunlight and frost.

**Coverage may vary depending on surface texture, porosity and application method.

*Under standard application conditions.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the wall surface is clean, dry, and free from dust, grease, or loose debris.

2



APPLY PRIMER

Apply a suitable base coat to ensure uniform adhesion and optimal performance of the texture.

3



APPLY TEXTURE

Evenly trowel or spray the LithoTex material to achieve the desired complex surface finish.

5. SAFETY FEATURES & PRECAUTIONS



Read the product label and technical data sheet before use.



Wear appropriate gloves and protective clothing during application.



Keep out of reach of children and away from food & feed.



Avoid contact with eyes. In case of contact, rinse thoroughly with water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



In case of spills, contain spillage using sand or earth.

6. STORAGE PRECAUTIONS



Store in a cool, dry place at ambient temperatures. Keep the container tightly closed when not in use.

7. RECOMMENDED FOR



- ✓ Exterior Residential Walls
- ✓ Commercial Building Facades
- ✓ Renovation Projects
- ✓ Architectural Feature Walls

8. HOW TO USE

- 1 Clean the surface and remove dust, grease, and loose particles.
- 2 Apply a suitable primer/base coat.
- 3 Apply LithoTex texture evenly.
- 4 Allow to dry completely. No curing required.

SCAN TO KNOW MORE



SCUFF
RESISTANT



ULTRA-MATTE
FINISH



ADVANCED
COLOR



WASHABLE
SURFACE