

LOTUSGUARD INTERIOR

Premium Interior Emulsion with Ultra Matte Finish and Lotus Technology.



LOW VOC



ECO FRIENDLY

2. AREAS OF APPLICATION



Walls



Ceilings



Interior Trim



Plasterboard

FEATURES AND BENEFITS

- ✓ **SUPERIOR WASHABILITY**
Resists stains and is easy to clean.
- ✓ **ANTI-STAIN TECHNOLOGY**
Repels common household liquids and spills.
- ✓ **ULTRA MATTE FINISH**
Delivers a sophisticated, non-reflective appearance.
- ✓ **DURABLE COATING**
Formulated for long-lasting performance on busy walls.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Polyurethane Dispersion

PHYSICAL PARAMETERS:

- Colour and appearance: White (viscous paste)
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 1.5 – 2 kg per sq. m in two coats for 1mm DFT

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Primer	Water	20L
Thinner	Water (approx. 10% dilution)	-
Thinner	Water (approx. 10% dilution)	-
Touch Dry	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
VOC Content	-	Low
Coverage	ISO 11890-1	10 – 12 sq m/L per coat

4. APPLICATION METHOD



SURFACE PREPARATION

Ensure surfaces are clean, dry, and free from dust and contaminants.
Apply suitable primer if required.



APPLICATION

Stir paint thoroughly. Apply by brush or roller.
Apply 1 coat of Epoxy Primer evenly.
Allow to dry for 4–6 hours before applying top coat.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MEDS for Waterproof Primer which gives detailed information safety measures while handling the paint, which is available on request.



Store the container with the lid tightly closed in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.




May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.

RECOMMENDED FOR



- ✓ New Convocation
- ✓ Renovation
- ✓ Damp prone areas
- ✓ Before Top Coat Application

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 1 coat of Epoxy Primer evenly.
- 3 Let it dry for 4–6 hours before applying top coat.



SUPERIOR
WASHABILITY



ANTI-STAIN
TECHNOLOGY



LOW ODOR
& LOW VOC



DURABLE
COATING



ECO FRIENDLY
& SAFE