



SURFACE PROTECTION EMULSION

LotusGuard

A premium emulsion providing durable, **ultra-smooth surface protection** with low odor and VOC.



AREAS OF APPLICATION

FEATURES AND BENEFITS



- ✔ Ultra-Smooth Finish
 - ✔ Excellent Durability & Washability
 - ✔ Low Odor & VOC
 - ✔ High Opacity & Coverage
- ✔ Superior Whiteness
 - ✔ Anti-Fungal Properties
 - ✔ Easy Application
 - ✔ Long-Lasting Protection

PRODUCT DETAILS

- Resin Type: Acrylic Copolymer
- Pigment: Titanium Dioxide & Functional Extenders

Parameter	Test Standard Used	Typical Values
Finish	Visual	Smooth Matt
Drying Time (Surface Dry)	ASTM D 1640	30 mins (Surface Dry), Recoat: 4 - 6 hrs.
Dilution	By Volume	Max. 40% with clean water
Coverage	Theoretical	12-14 sq. m/L/coat*
Sheen Level	ASTM D 523	5°-7° at 60° viewing angle
Shelf Life	-	24 months from date of manufacture in original sealed container

*Actual coverage may vary depending on surface condition and application method.

APPLICATION METHOD

SURFACE PREPARATION
Ensure the surface is clean, dry, and free from dust, grease, and loose material. Remove any existing paint or algae. Fill cracks and imperfections with a suitable wall putty. For fresh plaster, ensure it is fully cured.

PRIMING
Apply one coat of a suitable Water Based Wall Primer and allow it to dry completely (4-6 hours).

APPLICATION
Stir the contents well before use. Apply two coats of LotusGuard with a brush, roller, or spray, diluted as recommended. Maintain an interval of 4-6 hours between coats. Do not apply in direct sunlight or extreme humidity.

SAFETY FEATURES & PRECAUTIONS

Ensure good ventilation during application and drying.

Keep out of reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed, seek medical advice immediately and show this container or label.

Do not empty into drains or watercourses.

Dispose of contents/container in accordance with local regulations.

Wear suitable protective clothing, gloves, and eye/face protection.

Do not apply in direct sunlight or extreme humidity.

The product is lead-free and non-toxic under normal conditions.

STORAGE PRECAUTIONS
Store in a cool, dry place, away from direct sunlight and extreme temperatures. Keep container tightly closed when not in use.

RECOMMENDED FOR

- ✔ Interior Walls
- ✔ Exterior Walls
- ✔ Ceilings
- ✔ Gypsum Boards

