

METALLIC EMULSION

Lumina Emulsion

PREMIUM INTERIOR FINISH

HIGH-SHEEN LUMINOSITY

Luxurious metallic finish that elevates every surface with brilliance, durability & elegance.

WATER BASED

LEAD FREE GUARANTEE



- METALLIC HIGH-SHEEN FINISH
- EXCELLENT UV RADIATION RESISTANCE
- DUST & DIRT PICK UP RESISTANCE
- BRIGHTER, CLEANER SHADES
- ULTIMATE FILM INTEGRITY

1. AREAS OF APPLICATION



Ideal for interiors where you desire a rich, metallic high-sheen finish with superior aesthetics and performance.

2. FEATURES AND BENEFITS

- 

Premium metallic high-sheen finish
- 

100% acrylic water-based formula
- 

Excellent Dirt Pick Up Resistance (DPUR)
- 

Prevents dust settling, retains beauty
- 

Specially formulated high-performance pigments
- 

Outstanding UV radiation resistance
- 

Brighter, cleaner shades; fade resistant
- 

Ultimate film integrity

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Composition: 100% Acrylic Copolymer
- Finish: High-Performance Luxury Metallic

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Pack Sizes	-	100ml, 200ml, 500ml, 1L, 4L
Surface Dry Time	ASTM D 1640	15 – 30 minutes
Shades Available	-	40+

4. APPLICATION METHOD

- 

SURFACE PREPARATION

 - For masonry: should be cured for 28 days and have a moisture content of less than 5 – 10%.
 - Clean free of efflorescence, paint, dust, grease.
 - Remove algae growth before application.
 - Fill cracks up to 3mm with specialized filler.
 - For metal: remove rust by chipping, scraping, sanding to a smooth surface. Sand with 180-grit paper, followed by 320-grit paper. Apply specialized generic Masonry/Metal Primer.
- 

PRIMING

 - Remove rust by chipping, scraping, sand smooth. Sand with 180 paper.
 - Apply specialized generic Metal Primer. Sand with 320 paper.
- 

TOP COAT APPLICATION

 - Apply 2 coats of 'Lumina Emulsion' by brush, roller, or spray.
 - Allow 8 hours recoat time at 30°C and 50–60% humidity.
 - Some shades may require 3 coats.

5. SAFETY FEATURES & PRECAUTIONS

- Refer to the MSDS for Lumina Emulsion for detailed information.
- Available on request.
- Handle paint with safety measures.
- Surface dry 15–30 mins on cement panel.
- Dispose leftover properly.
- Consult local recycling agency.
- Avoid temperature <10°C & humidity >90%.
- Do not apply in rainy conditions.

6. STORAGE PRECAUTIONS

- 
- Store at a cool and dry place at ambient temperatures.
 - Keep container tightly closed when not in use.
- 

7. RECOMMENDED FOR

- 
- 

Masonry Surfaces
- 

Metal Surfaces
- 

Copper
- 

Mild Steel
- 

Wrought Iron

8. HOW TO USE

- 

Clean the surface and remove dust and loose particles.
- 

Apply Primer.
- 

Apply 2 coats of product evenly.
- 

Let it dry for 4–6 hours before applying top coat.

