

PREMIUM INTERIOR FINISH

Lumina Pro

ULTRA-PREMIUM WATER-BASED EMULSION

WITH SUPERIOR RECOAT AND FINISH.



STAIN
RESISTANT



ODORLESS



QUICK
DRY



ANTI-MICROBIAL
PROTECTION



WATER
BASED



QUICK
DRYING

1. AREAS OF APPLICATION



INTERIOR
WALLS



CEILING



MASONRY
PLASTER



WOODEN
SURFACES

Ideal for a wide range of interior surfaces providing long-lasting protection and enhanced appearance.

2. FEATURES AND BENEFITS

- ✓ Superior smoothness and finish
- ✓ Stain resistant and easy to clean
- ✓ Odorless and low VOC
- ✓ Anti-microbial and fungus protection
- ✓ Quick dry and easy recoat
- ✓ High color retention

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Acrylic Co-polymer Emulsion
- Water-based

PHYSICAL PARAMETERS:

- Colour Range: 48 shades available.
- Finish: Rich Sheen.
- Shelf life: 3 years from date of manufacture.
- Packaging: 1 ltr, 4 ltr, 10 ltr, 20 ltr packs.
- Stability of thinned paint: Use within 24 hours.

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish / Sheen	ISO 2813	Matt / ≤ 5 Units @ 85°
Coverage	ISO 6504-1	14 - 16 m ² /L/Coat*
Drying Time (Hard)	ASTM D1640	4 - 6 Hours
VOC Content	US EPA 24	Low VOC

*Coverage may vary depending on surface texture, porosity and application method.

4. APPLICATION METHOD



SURFACE PREPARATION

- Clean surface thoroughly with sanding paper to remove dust, grease, and loose particles.
- Fill cracks with acrylic wall putty.
- Sand smooth and ensure the surface is dry before painting.



PRIMING

- Apply one coat of water-based wall primer. Dilute with max 10% water. Allow to dry completely.



APPLICATION

- Apply two coats of Lumina Pro by roller or brush.
- Allow 3-4 hours drying time between coats.
- Sand lightly between coats for a flawless finish.

5. SAFETY FEATURES & PRECAUTIONS



Store in a cool,
dry place



Keep container
tightly closed
and upright



Keep out of
reach of
children



Use with
adequate
ventilation



Avoid
inhalation



Wear protective
gloves/eye
protection

6. STORAGE PRECAUTIONS



Store at ambient
temperatures and
protect from direct
sunlight.



7. HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply primer.
- 3 Apply two coats of Lumina Pro.
- 4 Allow 3-4 hours drying time between coats.



SUPERIOR
SMOOTHNESS



WEATHER & UV
RESISTANCE



EXCELLENT
COVERAGE



LONG LASTING
BEAUTY