

ARCHITECTURAL PAINTS

Lumix Sheen

Premium Low-Sheen Acrylic Emulsion



AREAS OF APPLICATION



Masonry Walls



Plaster



Concrete



Renovation Surfaces

FEATURES & BENEFITS

- Excellent Weather Resistance
- High Durability and Long Life
- Smooth, Low-Sheen Finish
- Exceptional Washability

- Excellent Opacity and Hiding
- Resists Fungal and Algal Growth
- Environmentally Friendly Formulation
- UV Resistant for Color Stability

PRODUCT DETAILS

- Product Type: Water-Based Acrylic Emulsion
- Finish: Low-Sheen
- Colors: Available in extensive shade range

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Specific Gravity	ASTM D 1475	1.25 - 1.35
Volume Solids	ISO 3233	38% - 42%
Viscosity	Brookfield	110 - 120 KU
Drying Time (Touch Dry)	ASTM D 1640	30 - 60 minutes
Recoat Time	Manufacturer Method	4 - 6 hours
Theoretical Coverage	ISO 6504-1	12 - 14 sq.m/L per coat

APPLICATION METHOD



SURFACE PREPARATION

Ensure surfaces are clean, dry, and free from dust, grease, and loose material. Remove any existing fungus or algae with a suitable solution. Repair cracks or imperfections with appropriate filler and allow to dry completely.



PRIMING

Apply one coat of COLORSOME® Wall Primer (water-based or solvent-based as required) to seal the surface and promote adhesion. Allow to dry completely.



APPLICATION

Stir Lumix Sheen thoroughly before use. Apply two coats using a brush, roller, or spray. Thin with up to 10% clean water if necessary. Allow 4-6 hours between coats.

SAFETY FEATURES & PRECAUTIONS



Keep out of reach of children.



Use appropriate personal protective equipment (gloves, goggles) during application.



Ensure good ventilation during application and drying.



Avoid contact with eyes and skin. In case of contact, rinse immediately with plenty of water and seek medical advice.



Do not empty into drains or watercourses.



Store in a cool, dry place, away from direct sunlight and heat sources.



Keep container tightly closed when not in use.



STORAGE PRECAUTIONS

Store in a cool, dry place. Keep away from frost and direct sunlight. Shelf life: 24 months from date of manufacture in unopened containers.

RECOMMENDED FOR



Interior Walls



Ceilings



Plasterboard



High-Traffic Areas



EXCEPTIONAL WASHABILITY



SCRUB RESISTANT



HIGH HIDING POWER



DURABLE FILM FORMATION



LOW ODOR & VOC