

INTERIOR WALL FINISH

Lustra Emulsion

Premium Interior Finish with Easy Clean Technology

Provides a beautiful, durable finish for modern interiors.



WATER BASED



LEAD FREE*
GUARANTEE



NO ADDED LEAD,
MERCURY OR
CHROMIUM

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



BEDROOM



LIVING ROOM



KITCHEN



OFFICE

Ideal for interior walls and ceilings in residential and commercial spaces.

2. FEATURES AND BENEFITS



Rich Finish

Provides excellent opacity and a vibrant, elegant finish.



Easy Clean

Resists common household stains and is easy to maintain.



Durable Protection

Long-lasting beauty with excellent washability.



Low VOC

Environment friendly formulation with low odour.



Safe Formula

Free from added lead, mercury and chromium.



Wide Range of Shades

Available in 1000+ attractive shades.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Acrylic Co-Polymer Emulsion

PHYSICAL PARAMETERS:

- Colour and appearance:** White (Smooth)
- Packaging:** 20 L
- Shelf life:** 2 years
- Coverage:** 10 – 12 sq m/L per coat at 25 microns DFT

TECHNICAL DATA

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	ASTM D523	Smooth Matt
Viscosity (at 25°C)	ASTM D562	90 – 110 KU
Drying Time (Surface Dry)	ASTM D1640	30 minutes
Recoating Time	ASTM D1640	4 – 6 hours
Dry Film Thickness (DFT)	ASTM D1186	25 – 35 microns per coat
Water Impermeability (72 hours)	BS EN 1062-3	No water penetration
Colour of Dry Film	Visual	White

4. APPLICATION METHOD



SURFACE PREPARATION

- New Concrete Plaster:** should be cured for at least 28 days and have a moisture content of less than 5 – 10%. Excessive laitance should be removed by mechanical methods. Dust and other loose material should be removed by vacuum cleaning. Any fine cracks or pin holes should be filled with epoxy-based mortar.
- Old Concrete Plaster:** damaged areas or surface irregularities should be repaired using epoxy-based mortar. All cracks larger than hairline shall be considered as moving and must be repaired with epoxy-based mortar.
- All delaminated and splashed areas of concrete shall be repaired prior to application of Polymer Modified Decorative Mortar (PMDM) with epoxy-based mortar.



PRIMING

- Apply one coat of universal recommended coverage of 80 – 100 Gram per square meter.

[Diluting ratio of Resin: Hardener: Water is 1 : 1 : 2 parts by weight]
- Allow primer to surface dry for 2 – 3 hours.



APPLICATION

- Before application, mix the material well with a mechanical mixer to get a homogeneous consistency. Apply mixed material with brush or roller at recommended coverage for first coat and allow to dry for 8 – 10 hours before second coat application, depending on the ambient conditions and surface temperature.
- Both coats should be applied at recommended dilution.
- Allow recoating after 4 – 6 hours depending on surface temperature.
- Ensure uniform coverage for best results.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for Lustra Emulsion for detailed safety information.



Wear appropriate gloves, mask and protective clothing during application.



Keep out of reach of children and away from eatables.



Wear eye protection during application. In case of eye contact, rinse immediately with plenty of water and seek medical advice.



Wash skin with soap and water.



Do not pour leftover paint down the drain or in other courses.



No added Lead, Mercury or Chromium compounds.

6. STORAGE PRECAUTIONS



- Store in a cool and dry place at ambient temperatures.
- Keep containers tightly closed when not in use.
- Protect from moisture, frost and direct sunlight.
- Shelf life: 24 months from date of manufacture.



RECOMMENDED FOR



- All interior masonry
- Concrete
- Plaster surfaces

HOW TO USE

- Clean the surface properly.
- Apply universal primer evenly.
- Apply 2 coats of Lustra Emulsion evenly.
- Allow to dry completely.
- Enjoy a beautiful, long-lasting finish.



RICH
FINISH



EASY
CLEAN



DURABLE
PROTECTION



LOW
VOC



SAFE
FORMULA