

INTERIOR EMULSION

Lustra Teflon Pro

Ultra-premium, durable,
easy-clean finish for interior walls

- 

Easy Clean
Technology
- 

Advanced
Stain Resistance
- 

High
Durability
- 

Excellent
Finish
- 

Low VOC
Better IAQ



AREAS OF APPLICATION



Living Room



Bedroom



Hallway



Study

FEATURES & BENEFITS



Easy-Clean Technology



Advanced Stain Resistance:
Repels common household
stains.



High Durability



Excellent Finish:
Smooth, rich appearance.



Highly washable finish.



Repels common household stains.



Excellent Finish: Smooth,
rich appearance.



Anti-Fungal: Resists fungal
growth.



Low VOC: Better indoor air quality.

PRODUCT DETAILS

- Finish: Rich Matte
- Opacity: Excellent Hiding
- Viscosity: Optimized for smooth application

TECHNICAL INFORMATION

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Spreading Rate (per coat)*	ISO 6504-1	12-14 sq. m/L
Drying Time: Surface Dry	ASTM D1640	30 minutes
Drying Time: Hard Dry	ASTM D1640	4-6 hours
Recoat Time	ISO 9117-1	Min. 3-4 hours
VOC Content	ISO 11890-2	< 15 g/L
Shelf Life	Manufacturer Spec	36 months from mfg.

*Actual coverage may vary depending on surface texture and application method.

APPLICATION METHOD



1. SURFACE PREPARATION

Ensure surfaces are sound, clean, dry, and free from loose paint, dust, grease, and wax.

Remove existing loose paint by sanding.

Treat fungal growth with a suitable solution.



2. PRIMING

Apply one coat of 'COLORSOME' Wall Primer (Water or Solvent Based) depending on substrate.

Allow to dry.



3. APPLICATION

Stir contents well before use.

Apply two coats of 'Lustra Teflon Pro' by roller or brush, thinned with up to 5-10% clean water if required.

Allow 3-4 hours between coats.

SAFETY FEATURES & PRECAUTIONS



Keep out of reach of children.



Wear suitable protective clothing, gloves, and eye/face protection during application.



Ensure good ventilation during application and drying.



In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not empty into drains or watercourses. Dispose of waste in accordance with local regulations.



Store in a cool, dry place, away from direct sunlight and sources of heat.



Store container tightly closed.



STORAGE PRECAUTIONS

Store container upright and tightly closed in a cool, dry, well-ventilated area. Protect from frost and extreme heat.



RECOMMENDED FOR

- Interior Walls, Ceilings
- Plaster, Gypsum Board
- Concrete

Easy Clean
Technology

Advanced
Stain Resistance

High
Durability

Excellent
Finish

Low VOC
Better IAQ