

Luxura Pro

PREMIUM INTERIOR ENAMEL

Luxura Pro is an ultra-premium, water-based interior emulsion for luxurious finishes.

- ULTRA SMOOTH FINISH
- EXCELLENT COVERAGE
- LOW VOC FORMULA
- FADE RESISTANT



- WATER BASED
- LEAD FREE* GUARANTEE
- LOW VOC FOR HEALTHY INDOOR AIR

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION

- PLASTERED WALLS
- CONCRETE SURFACES
- DRYWALL
- MASONRY

Ideal for interior surfaces that demand a luxurious finish with long-lasting beauty.

2. FEATURES AND BENEFITS

- Easy to apply by brush and roller
- Exceptional coverage and hiding power
- Ultra-smooth finish with elegant sheen
- Excellent resistance to scrubbing and stains
- Low VOC for healthy indoor air
- Water-based and quick drying
- Fade-resistant and long-lasting
- Excellent touch-up properties

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Polymer type: Acrylic Emulsion
- Pigment type: Rutile Titanium Dioxide and extenders
- Specific Gravity: Approx. 1.35
- Shelf Life: 2 Years

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Appearance	White (smooth liquid)	-
Weight Per Liter	ASTM D 1475	1.35 kg
Viscosity	ASTM D 562	105 - 110 KU
Volume Solids	ISO 3233	40 ± 2%
Hiding Power	ASTM D 2805	≥ 0.98
Wet Scrub Resistance	ISO 11998	Class 1
VOC Content	EPA Method 24	<10g/L

**Coverage may vary depending on surface porosity, texture, application method and color shade.

4. APPLICATION METHOD

- SURFACE PREPARATION**
 - New Concrete Plaster:** should be cured for at least 28 days old and have a moisture content of less than 5–10%. Excessive laitance should be removed by mechanical methods. Dust and other details should be removed by vacuum cleaning. Any fine cracks or pin holes should be covered with Epoxy-based mortar.
 - Old Concrete Planer:** damaged areas of surface insulations should be repaired using epoxy-based mortar. All cracks larger than hairline shall be considered as moving and must be repaired with epoxy-based mortar. All delaminated and splashed areas of concrete shall be repaired prior to application of PDD with epoxy-based mortar.
- PRIMING**
 - Apply one coat of Colorsome Water-Based Primer at the recommended coverage.
 - Ensure the primer is compatible with the substrate and allow it to dry completely.
 - For highly absorbent or porous surfaces, apply a second coat of Colorsome Water-Based Primer if required.
 - Allow the primer to dry for 4–6 hours before applying the first coat of the finish.
- APPLICATION OF LUXURA PRO**
 - Stir thoroughly before use.
 - Apply 2 coats of Luxura Pro using a high-quality brush or roller.
 - Allow 4–6 hours drying time between coats.
 - For best results, avoid overthinning.

5. SAFETY FEATURES & PRECAUTIONS

- Refer to MSDS for detailed safety information.
- Keep out of reach of children and away from eatables.
- Avoid contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of water.
- Do not empty into drains or watercourses.
- Dispose of container safely and responsibly.

STORAGE PRECAUTIONS

- Store in a cool and dry place at ambient temperatures.
- Store the container with the lid tightly closed in an upright position.
- Store away from direct sunlight and heat.

RECOMMENDED FOR

- New Construction
- Renovation
- Living Areas
- Bedrooms
- High Traffic Zones
- Hotels & Hospitality
- Offices & Commercial Interiors

HOW TO USE

- Clean the surface and remove dust and loose particles.
- Apply 1 coat of Colorsome Water-Based Primer evenly.
- Let it dry for 4–6 hours before applying 1st coat of Luxura Pro.

