

METALOCK RED PRO

PREMIUM METAL PRIMER RED OXIDE

SUPERIOR PROTECTION. HIGH VISIBILITY. BUILT TO LAST.

Metalock Red Pro is a premium metal primer formulated with advanced technology to deliver exceptional protection, excellent adhesion and a high-visibility red finish for the most demanding industrial environments.

- 

HEAVY-DUTY PROTECTION
- 

CHEMICAL RESISTANT
- 

HIGH VISIBILITY
- 

LONG-LASTING



- 

HEAVY-DUTY PROTECTION
Provides excellent barrier protection against rust, corrosion and harsh industrial conditions.
- 

CHEMICAL RESISTANT
Resists exposure to oils, chemicals and industrial fumes for enhanced durability.
- 

HIGH VISIBILITY
High-visibility red finish improves safety and visibility in critical industrial areas.
- 

LONG-LASTING
Advanced formulation ensures long-term performance and extended service life.

1. WHY CHOOSE METALOCK RED PRO?

- 

Heavy-duty Protection
Advanced anti-corrosive formula provides maximum protection for metal structures and equipment.
- 

Chemical Resistant
Withstands exposure to chemicals, oils, solvents and industrial fumes.
- 


High Visibility
Bright red oxide finish enhances visibility and safety in industrial environments.
- 


Long-lasting
Superior adhesion and durability ensure a long service life with minimal maintenance.

2. IDEAL FOR

- 

Fire Safety Equipment
Fire hydrants, cabinets, extinguishers and safety installations.
- 

Heavy Machinery
Earthmoving equipment, machines and industrial vehicles.
- 

Industrial Piping
Pipelines, valves, fittings and storage tanks.
- 

Warning Markings
Safety signs, hazard markings and high-risk area identification.

Designed for indoor and outdoor industrial metal applications.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Red Oxide Primer
- Finish : Matt
- Colour : Red Oxide
- Viscosity : 90 – 110 KU @ 25°C
- Solid by Volume : 40 ± 2%
- Specific Gravity : 1.30 ± 0.05
- Drying Time (Touch Dry) : 20 – 40 mins
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 6 – 8 hrs
- Coverage : 10 – 12 m²/litre/coat*
- No. of Coats : 1 – 2 Coats
- Thinner : Epoxy / Synthetic Thinner
- Packaging : 1L, 4L, 10L, 20L

* Coverage may vary depending on surface type, texture and application method.


PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Corrosion Resistance	Excellent
Adhesion	Excellent (5B)
Weather Resistance	Excellent
Abrasion Resistance	Good
Impact Resistance	Good
Flexibility	Moderate
Heat Resistance	Up to 80°C
Salt Spray Resistance	Excellent
Chemical Resistance	Good
Coverage	10 – 12 m²/litre

4. SURFACE PREPARATION & APPLICATION GUIDE

- 


1. SURFACE PREPARATION

 - Remove loose paint, rust, dust, oil and grease.
 - Clean the surface thoroughly with wire brush or sandpaper.
 - Surface should be dry and free from moisture.
- 


2. PRIMING

 - Stir the primer thoroughly before use.
 - Apply 1 coat of Metalock Red Pro using brush, roller or spray.
 - Ensure uniform and even application.
- 

3. DRYING

 - Touch dry in 20 – 40 mins.
 - Hard dry in 4 – 6 hrs.
 - Recoat after 6 – 8 hrs.
- 

4. TOPCOAT APPLICATION

 - Apply compatible topcoat such as Synthetic Enamel / PU Paint for better protection and finish.
 - Allow proper drying between coats.
- 

5. CLEANING

 - Clean all tools and equipment immediately after use with thinner.
 - Do not allow paint to dry on tools.

5. SAFETY FEATURES & PRECAUTIONS

- 

Refer to MSDS for complete safety information.
- 

Keep out of reach of children.
- 

Wear protective gloves, mask and goggles during application.
- 

In case of contact with eyes, rinse immediately with plenty of water.
- 

If swallowed, seek medical advice immediately.
- 

Ensure adequate ventilation during application and drying.
- 

Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS

- 
- Store in a cool, dry place.
 - Keep containers tightly closed when not in use.
 - Protect from direct sunlight, heat and moisture.
 - Shelf life: 24 months from

RECOMMENDED FOR

- ✓ Fire Safety Equipment
- ✓ Heavy Machinery
- ✓ Industrial Piping
- ✓ Warning Markings
- ✓ Industrial Projects

HOW TO USE

- 1 Prepare the surface properly.
- 2 Apply 1 coat of Metalock Red Pro.
- 3 Allow proper drying time.
- 4 Apply recommended topcoat for enhanced protection.

SCAN TO KNOW MORE

