

# METALOCK RED

## METAL PRIMER RED OXIDE

RELIABLE PROTECTION. STANDARD RED FINISH.

Metalock Red offers reliable protection and a standard red oxide finish for general industrial metal coating requirements. It ensures good adhesion, durability and long-lasting performance on metal surfaces.



**GOOD ADHESION**



**WEATHER RESISTANT**



**ECONOMICAL**



**EASY TO APPLY**





**GOOD ADHESION**  
Ensures strong bonding with metal surfaces for long-lasting performance.



**WEATHER RESISTANT**  
Withstands harsh weather conditions and protects against corrosion.



**ECONOMICAL**  
Cost-effective solution for general industrial coating needs.



**EASY TO APPLY**  
Can be applied easily by brush, roller or spray for smooth and even coating.

### 1. WHY CHOOSE METALOCK RED?



**Good Adhesion**  
Provides reliable bonding to a wide range of metal surfaces.



**Weather Resistant**  
Protects metal surfaces from moisture, corrosion and environmental damage.



**Economical**  
Offers excellent performance at an affordable cost.



**Easy to Apply**  
Suitable for brush, roller or spray application for quick and uniform coverage.

### 2. IDEAL FOR



**General Metal Surfaces**  
Suitable for mild steel, iron and other metal substrates.



**Maintenance Work**  
Ideal for regular maintenance and protective coating.



**Repairs**  
Provides effective protection for repaired metal areas.



**Touch-ups**  
Perfect for spot repairs and touch-up applications.

Ideal for indoor and outdoor industrial metal applications.

### 3. PRODUCT DETAILS

#### TECHNICAL SPECIFICATIONS

- Type : Red Oxide Primer
- Finish : Matt
- Colour : Red Oxide
- Viscosity : 90 – 110 KU @ 25°C
- Solid by Volume : 40 ± 2%
- Specific Gravity : 1.30 ± 0.05
- Drying Time (Touch Dry) : 20 – 40 mins
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 6 – 8 hrs
- Coverage : 10 – 12 m²/litre/coat\*
- No. of Coats : 1 – 2 Coats
- Thinner : Epoxy / Synthetic Thinner
- Packaging : 1L, 4L, 10L, 20L

\* Coverage may vary depending on surface type, texture and application method.

#### PERFORMANCE PROPERTIES

| PROPERTY              | TYPICAL VALUE    |
|-----------------------|------------------|
| Corrosion Resistance  | Good             |
| Adhesion              | Good (4B)        |
| Weather Resistance    | Good             |
| Abrasion Resistance   | Good             |
| Impact Resistance     | Good             |
| Flexibility           | Moderate         |
| Heat Resistance       | Up to 80°C       |
| Salt Spray Resistance | Good             |
| Coverage              | 10 – 12 m²/litre |

### 4. SURFACE PREPARATION & APPLICATION GUIDE



#### 1. SURFACE PREPARATION

- Remove loose paint, rust, dust, oil and grease.
- Clean the surface thoroughly with wire brush or sandpaper.
- Surface should be dry and free from moisture.



#### 2. PRIMING

- Stir the primer thoroughly before use.
- Apply 1 coat of Metalock Red using brush, roller or spray.
- Ensure uniform and even application.



#### 3. DRYING

- Touch dry in 20 – 40 mins.
- Hard dry in 4 – 6 hrs.
- Recoat after 6 – 8 hrs.



#### 4. TOPCOAT APPLICATION

- Apply compatible topcoat such as Synthetic Enamel / PU Paint for better protection and finish.
- Allow proper drying between coats.




#### 5. CLEANING

- Clean all tools and equipment immediately after use with thinner.
- Do not allow paint to dry on tools.

### 5. SAFETY FEATURES & PRECAUTIONS




Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, mask and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

#### STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, heat and moisture.
- Shelf life: 24 months from date of manufacture.

#### RECOMMENDED FOR

- General Metal Surfaces
- Maintenance Work
- Repairs
- Touch-ups
- Industrial Applications

#### HOW TO USE

- Prepare the surface properly.
- Apply 1 coat of Metalock Red.
- Allow proper drying time.
- Apply recommended topcoat for enhanced protection.

#### SCAN TO KNOW MORE

