

METALOCK YELLOW PRO

PREMIUM METAL PRIMER
YELLOW OXIDE

Professional grade yellow metal
coating for industrial use.

Metalock Yellow Pro is a professional-grade
coating specifically formulated for metal
surfaces requiring high visibility and protection.


HIGH
VISIBILITY


CORROSION
RESISTANT


UV
STABLE


INDUSTRIAL
GRADE



**HIGH VISIBILITY**
Bright yellow finish
for clear identification.

**CORROSION
RESISTANT**
Protects metal from
rust and deterioration.

**UV STABLE**
Maintains color
under harsh sunlight.

**INDUSTRIAL GRADE**
Engineered for
heavy-duty environments.

1. WHY CHOOSE METALOCK YELLOW PRO?

**High Visibility**
Bright yellow finish for clear
identification and safety.

**Corrosion Resistant**
Forms a protective barrier
against rust and oxidation.

**UV Stable**
Withstands harsh sunlight
and extreme weather.

**Industrial Grade**
Long-lasting protection for
heavy-duty applications.

2. IDEAL FOR

**Safety Equipment**
High-visibility coating for
critical gear.

**Industrial Machinery**
Protects equipment
and metal parts.

**Markings**
Ensures clear and
durable identification.

**Heavy Equipment**
Withstands tough
industrial conditions.

**Perfect for high-wear
and outdoor metal surfaces.**

3. TECHNICAL SPECIFICATIONS

Property	Typical Value
Colour	Yellow
Finish	Matt / Semi-Gloss
Viscosity	85 – 95 KU @ 25°C
Solid by Volume	50 ± 2%
Drying Time (Touch)	30 – 45 minutes
Drying Time (Hard)	4 – 6 hours
Recoating Time	4 – 6 hours
Coverage	10 – 12 m ² /litre
Thinner	Clean Water
Packaging	1L, 4L, 10L, 20L

4. SURFACE PREPARATION & APPLICATION GUIDE

**1. SURFACE PREPARATION**

- Surface must be clean, dry and free from dust, oil, grease and loose paint.
- Remove all rust and flaking material.

**2. PRIMING**

- Stir well before use.
- Apply 1 coat of Metalock Yellow Pro using brush, roller or spray.

**3. DRYING**

- Touch dry in 30 – 45 minutes.
- Hard dry in 4 – 6 hours.

**4. APPLICATION**

- Apply 1–2 coats for best results.
- Maintain even coat thickness.

**5. CLEANING**

- Clean all tools with water immediately after use.

5. SAFETY FEATURES & PRECAUTIONS

**Wear protective goggles and gloves.**

**Use in well-ventilated areas.**

**Keep away from open flames.**

**In case of contact with skin or eyes, wash immediately with water.**

**Dispose of containers as per local regulations.**

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, heat and moisture.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

- ✓ Safety Equipment
- ✓ Industrial Machinery
- ✓ Markings
- ✓ Heavy Equipment
- ✓ Metal Structures

HOW TO USE

- 1 Prepare the surface properly.
- 2 Stir the paint well.
- 3 Apply 1–2 coats.
- 4 Allow to dry completely.
- 5 Achieve durable, long-lasting protection.

SCAN TO KNOW MORE

