

METALOCK YELLOW

METAL PRIMER YELLOW OXIDE

RELIABLE PROTECTION. BRIGHT PERFORMANCE.

Metalock Yellow is a reliable metal primer that provides excellent protection and a high-visibility yellow finish for general metal coating applications.



DURABLE FINISH



GOOD COVERAGE



WEATHER RESISTANT



EASY APPLICATION

COLORSOME®
METALOCK YELLOW
METAL PRIMER YELLOW OXIDE





DURABLE FINISH



GOOD COVERAGE



WEATHER RESISTANT



EASY APPLICATION

FOR GOOD ADHESION AND PERFORMANCE OF THE PRIMER FILM ON METAL SURFACE



DURABLE FINISH
Provides a tough and durable coat that protects metal surfaces from wear and tear.



GOOD COVERAGE
Excellent hiding power ensures uniform finish with fewer coats.



WEATHER RESISTANT
Withstands harsh weather conditions and prevents rust and corrosion.



EASY APPLICATION
Smooth application by brush, roller or spray for hassle-free painting.

1. WHY CHOOSE METALOCK YELLOW?



Durable Finish
Provides a long-lasting, hard-wearing coat that protects metal surfaces effectively.



Good Coverage
High hiding power ensures uniform coverage and excellent opacity with fewer coats.



Weather Resistant
Resists moisture, humidity and corrosive environment for extended protection.



Easy Application
Can be easily applied using brush, roller or spray for smooth and even finish.

2. IDEAL FOR



Metal Structures
Factories, warehouses, sheds and structural steel.



Pipes
Water pipes, pipelines and metal conduits.



Equipment
Industrial equipment, tools and fabricated components.



General Metal Work
Grills, gates, railings and general metal surfaces.

Suitable for both indoor and outdoor metal applications.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Red Oxide Primer
- Finish : Matt
- Colour : Yellow Oxide
- Viscosity : 90 – 110 KU @ 25°C
- Solid by Volume : 40 ± 2%
- Specific Gravity : 1.30 ± 0.05
- Drying Time (Touch Dry) : 20 – 40 mins
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 6 – 8 hrs
- Coverage : 10 – 12 m²/litre/coat*
- No. of Coats : 1 – 2 Coats
- Thinner : Epoxy / Synthetic Thinner
- Packaging : 1L, 4L, 10L, 20L

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Corrosion Resistance	Good
Adhesion	Good (4B)
Weather Resistance	Good
Abrasion Resistance	Good
Impact Resistance	Good
Flexibility	Moderate
Heat Resistance	Up to 80°C
Salt Spray Resistance	Good
Coverage	10 – 12 m²/litre

* Coverage may vary depending on surface type, texture and application method.

4. SURFACE PREPARATION & APPLICATION GUIDE



1. SURFACE PREPARATION

- Remove loose paint, rust, dust, oil and grease.
- Clean the surface thoroughly with wire brush or sandpaper.
- Surface should be dry and free from moisture.



2. PRIMING

- Stir the primer thoroughly before use.
- Apply 1 coat of Metalock Yellow using brush, roller or spray.
- Ensure uniform and even application.




3. DRYING

- Touch dry in 20 – 40 mins.
- Hard dry in 4 – 6 hrs.
- Recoat after 6 – 8 hrs.



4. TOPCOAT APPLICATION

- Apply compatible topcoat such as Synthetic Enamel / PU Paint for better protection and finish.
- Allow proper drying between coats.



5. CLEANING

- Clean all tools and equipment immediately after use with thinner.
- Do not allow paint to dry on tools.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, mask and goggles during application.




In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.




Dispose of empty containers as per local regulations.




STORAGE PRECAUTIONS

- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, heat and moisture.
- Shelf life: 24 months from date of manufacture.



RECOMMENDED FOR

- Metal Structures
- Pipes
- Equipment
- General Metal Work
- Industrial Projects



HOW TO USE

- Prepare the surface properly.
- Apply 1 coat of Metalock Yellow.
- Allow proper drying time.
- Apply recommended topcoat for enhanced durability.



DURABLE FINISH

GOOD COVERAGE

WEATHER RESISTANT

EASY APPLICATION

RELIABLE PROTECTION