

NANOSHIELD EXT

EXTERIOR NANO-PARTICLE SHIELD COATING

Protect your home with NanoShield Ext, the ultimate weather-resistant finish for a pristine, long-lasting exterior. Engineered with advanced Nano Block and Silicone stitch technologies, this premium emulsion shields your walls against harsh weather and dirt accumulation. Its anti-algal, low-VOC formula provides a safe, durable, and brilliant finish that meets international sustainability standards.



ADVANCED
NANO BLOCK
SHEEN



DUST PROOF
SURFACE
TECHNOLOGY



WEATHER-
RESISTANT
SILICONE
PROTECTION



ECO-FRIENDLY,
LOW VOC
FORMULATION



STAIN
REPELLENT



ULTRA
DURABLE



WATER
REPELLENT



WASHABLE
COLOR

2. AREAS OF APPLICATION



EXTERIOR MASONRY WALLS

FEATURES AND BENEFITS



ADVANCED NANO BLOCK SHEEN

Forms a nano-level protective layer that enhances the sheen and keeps your walls looking new for longer.



DUST PROOF SURFACE TECHNOLOGY

Prevents dirt and dust from settling on the surface, ensuring cleaner walls with minimal maintenance.



WEATHER-RESISTANT SILICONE PROTECTION

Offers superior resistance to rain, UV rays, and extreme weather conditions.



ECO-FRIENDLY, LOW VOC FORMULATION

Low VOC and anti-algal formula ensures a healthy environment and safe living.

3. PRODUCT DETAILS

Type: Exterior Emulsion Paint

Finish: Elegant Sheen

Colour: As per shade card

Coverage: 10–12 sq m/L/coat*

Packaging: 20 L

Shelf Life: 3 years

Application: Exterior masonry walls

*Coverage may vary depending on surface texture and porosity.

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Sheen Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoating Time	ASTM D 1640	4 – 6 hours
Coverage	ISO 11890-1	10 – 12 sq m/L/coat*
Washability	IS 9845	Excellent
Water Resistance	Internal Method	Excellent
VOC Content	As per BIS Standards	Low
Anti-Algal	Internal Method	Effective
Application Method	—	Brush, Roller, Spray
Recommended Thinning	—	Up to 10% with clean water

4. APPLICATION METHOD



1. PREPARE SURFACE

Ensure the exterior surface is clean, dry, and free from loose paint, dust, or contaminants.



2. APPLY PRIMER

Apply a suitable coat of primer to create a uniform base for enhanced paint adhesion.



3. APPLY TOPCOAT

Apply two to three coats of NanoShield Ext using a brush, roller, or spray for complete protection.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the Safety Data Sheet (SDS) for detailed information on safe handling and usage.



Store the container with the lid tightly closed in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, mercury or chromium compounds.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures. Protect from direct sunlight and frost.

RECOMMENDED FOR



- Residential Buildings
- Commercial Buildings
- Institutional Projects
- Hospitality Buildings

HOW TO USE

- Clean the surface and remove dust, oil, or loose particles.
- Apply the primer as per recommendation.
- Let it dry for 4–6 hours before applying top coat.

