

PROTECTIVE COATINGS

Nanoshield Pro

ADVANCED PROTECTIVE COATING

A premium hydrophobic coating that repels water, resists stains and shields your surfaces for longer.



ULTRA-MATTE
FINISH



HYDROPHOBIC
TECHNOLOGY



LONG-LASTING
PROTECTION

1. AREAS OF APPLICATION



UV
PROTECTION



WATER & DUST
REPELLENT



STAIN & ALKALI
RESISTANT



EASY TO
CLEAN

Ideal for walls, exteriors, interiors, concrete, masonry and other mineral surfaces.

2. FEATURES AND BENEFITS

- Repels water and dust effectively
 - Provides anti-UV protection
 - Resists stain and alkali
- Highly durable for long-lasting performance
 - Easy to clean surface
 - Resist, Repel, Shield technology

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Hydrophobic Coating Dispersion

- Hydrophobic Coating
- Gloss Level
- Drying Time

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Gloss Level	[SPEC SHEET AVAILABLE UPON REQUEST]	[SPEC SHEET AVAILABLE UPON REQUEST]
Hydrophobicity	[SPEC SHEET AVAILABLE UPON REQUEST]	[SPEC SHEET AVAILABLE UPON REQUEST]
Drying Time	[SPEC SHEET AVAILABLE UPON REQUEST]	[SPEC SHEET AVAILABLE UPON REQUEST]

4. APPLICATION METHOD



SURFACE PREPARATION

Ensure surface is clean, dry and free of contaminants.



SEE TECHNICAL
DATASHEET FOR
FULL DETAILS



APPLICATION

Apply two coats at recommended coverage.



SEE TECHNICAL
DATASHEET FOR
FULL DETAILS



CURING

Allow to dry for 4-6 hours before applying top coat.



SEE TECHNICAL
DATASHEET FOR
FULL DETAILS

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for detailed information



Keep out of reach of children



Avoid contact with eyes and skin



Ensure good ventilation during application



Do not empty into drains



SEE TECHNICAL
DATASHEET FOR FULL
PRECAUTIONS

STORAGE PRECAUTIONS



- Store in a cool and dry place at ambient temperatures.
- Keep container tightly closed when not in use.

RECOMMENDED FOR

- New Construction
- Renovation
- Damp prone areas
- Before Top Coat Application

HOW TO USE

- Clean the surface and remove dust and loose particles.
- Apply 2 coat of Epoxy Primer evenly.
- Let it dry for 4-6 hours before applying top coat.



ULTRA-MATTE
FINISH



HYDROPHOBIC
TECHNOLOGY



LONG-LASTING
PROTECTION



ANTI-UV
PROTECTION



PREMIUM
QUALITY