

Nanoshield

ADVANCED PROTECTIVE COATING PREMIUM FINISH

Protect your home with Nanoshield, the advanced exterior emulsion featuring superior anti-dust and UV-blocking technology.

Engineered with a modified acrylic formula and silicon additives, Nanoshield offers a smooth, durable finish that withstands harsh climates. Its unique nano-block technology prevents dust settlement while providing exceptional resistance against algal growth and color fading.



-  **NANO-BLOCK DUST RESISTANCE**
-  **SUPERIOR ALGAL GROWTH PREVENTION**
-  **ADVANCED UV FADE PROTECTION**
-  **ECO-FRIENDLY LOW VOC**

2. AREAS OF APPLICATION



-  **ALL EXTERIOR WALL SURFACES**
 -  **BUILDINGS IN HARSH CLIMATES**
- Ideal for all types of exterior masonry surfaces including cement plaster, concrete, brickwork, and previously painted walls.

3. FEATURES AND BENEFITS

-  **NANO-BLOCK DUST RESISTANCE**
Advanced nano technology prevents dust settlement, keeping your walls cleaner for longer.
-  **SUPERIOR ALGAL GROWTH PREVENTION**
Special additives inhibit algae and fungal growth, ensuring a healthy surface.
-  **ADVANCED UV FADE PROTECTION**
High performance UV blockers protect against color fading and maintain vibrancy.
-  **ECO-FRIENDLY LOW VOC FORMULATION**
Low VOC content ensures a safer environment and is better for your family.

4. PRODUCT DETAILS

- Type** : Exterior Emulsion Paint
- Finish** : Smooth
- Colour** : As per Shade Card
- Packaging** : 1 L, 4 L, 10 L, 20 L
- Shelf Life** : 3 years from date of manufacture
- Application** : Exterior walls; Harsh climates

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Uniform Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Washability	Internal Method	Excellent
Algal Resistance	Internal Method	Excellent
UV Resistance	Internal Method	Excellent
Coverage	Internal Method	10 – 12 sq m/L/coat*
Application Method	-	Brush, Roller, Spray
VOC Content	ISO 11890-1	Low (LEED VOC Compliant)

*Coverage may vary depending on surface texture and porosity.

5. HOW TO APPLY

-  **1. PREPARE SURFACE**
Ensure all exterior surfaces are clean, dry, and free from loose paint, dust, or contaminants.
-  **2. APPLY PRIMER**
Apply a suitable exterior primer to ensure optimal adhesion and long-lasting performance of the emulsion.
-  **3. PAINT APPLICATION**
Apply two to three coats of Nanoshield evenly, allowing for standard drying time between each layer.



6. SAFETY FEATURES & PRECAUTIONS

-  Read the Safety Data Sheet (SDS) carefully before use.
-  Keep out of reach of children and away from eatables.
-  Do not pour leftover paint down the drain or in water bodies.
-  Wear eye protection during application. In case of contact, rinse with plenty of water.
-  Store the container tightly closed in a cool, dry place away from direct sunlight and heat.
-  May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
-  In the event of spills, contain spillage using sand or earth.
-  No added lead, mercury, or chromium compounds.

7. STORAGE PRECAUTIONS

-  Store in a cool and dry place at ambient temperatures. Protect from extreme heat, freezing, and direct sunlight.

8. RECOMMENDED FOR

-  Residential Buildings
-  Commercial Buildings
-  Institutional Projects
-  Renovation Projects

9. WHY CHOOSE NANOSHIELD?

-  Advanced nano-block technology
-  Long-lasting, durable performance
-  Resists harsh weather conditions
-  Keeps surfaces cleaner for longer
-  Value for money solution

