



OIL PAINT

PREMIUM

PREMIUM OIL-BASED PAINT

SUPERIOR FINISH. LASTING BEAUTY.

Oil Paint Premium delivers a superior, durable finish with excellent flow and leveling properties, ensuring a smooth, rich appearance and long-lasting protection for a wide range of surfaces.

- 

SUPERIOR FLOW
- 

EXCELLENT DURABILITY
- 

HIGH GLOSS OPTION
- 


SMOOTH FINISH



- 

SUPERIOR FLOW
Excellent flow and leveling for a flawless finish.
- 

EXCELLENT DURABILITY
Tough and durable film for long-lasting performance.
- 

HIGH GLOSS OPTION
Available in high gloss for enhanced beauty and shine.
- 

SMOOTH FINISH
Smooth, even finish for a professional look.

1. WHY CHOOSE OIL PAINT PREMIUM?

- 

Superior Flow
Provides excellent flow and leveling for a flawless, streak-free finish.
- 

Excellent Durability
Forms a tough, hard film that withstands wear, tear and daily use.
- 

High Gloss Option
Available in high gloss to enhance the depth, richness and beauty of your surfaces.
- 

Smooth Finish
Delivers a smooth, even finish that brings out the best in every application.

2. IDEAL FOR

- 

Fine Woodwork
Doors, windows, trim and wooden fixtures.
- 

Furniture
Tables, chairs, cabinets and wooden furniture.
- 

Decorative Surfaces
Moldings, panels and architectural details.
- 

Artistic Projects
Canvas, boards and other artistic applications.

Ideal for both interior and exterior applications.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Oil Based Paint
- Finish : Matt, Satin, Gloss, High Gloss
- Colour : As per shade card
- Viscosity : 90 – 110 KU @ 25°C
- Solid by Volume : 45 ± 2%
- Specific Gravity : 0.90 – 1.10
- Drying Time (Touch Dry) : 6 – 8 hrs
- Drying Time (Hard Dry) : 16 – 24 hrs
- Recoat Time : 16 – 24 hrs
- Coverage : 12 – 16 m²/litre/coat*
- No. of Coats : 2 – 3 Coats
- Thinner : Oil Paint Thinner
- Packaging : 1L, 4L, 10L, 20L

* Coverage may vary depending on surface type, texture and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Flow & Leveling	Excellent
Adhesion	Excellent
Durability	Excellent
Gloss (High Gloss Option)	85 – 95 GU @ 60°
Weather Resistance	Good
Impact Resistance	Good
Hardness	Good
Flexibility	Moderate
Chemical Resistance	Good
Heat Resistance	Up to 80°C
Coverage	12 – 16 m ² /litre

4. SURFACE PREPARATION & APPLICATION GUIDE

- 

1. SURFACE PREPARATION

 - Surface must be clean, dry and free from dust, dirt, grease, oil or loose paint.
 - Sand the surface smoothly and wipe clean.
 - Fill cracks and holes and allow to dry.
- 


2. PRIMING

 - Apply suitable oil-based primer (Red Oxide Primer recommended) and allow it to dry.
 - Sand lightly if required.
- 

3. STIRRING

 - Stir the paint thoroughly before use and occasionally during application.
- 

4. APPLICATION

 - Apply 2 – 3 coats using a quality brush, roller or spray.
 - Allow proper drying time between coats.
- 

5. CLEANING

 - Clean all tools and equipment immediately after use with Oil Paint Thinner.

5. SAFETY FEATURES & PRECAUTIONS

- 

Refer to MSDS for complete safety information.
- 

Keep out of reach of children.
- 

Wear protective gloves, mask and goggles during application.
- 

In case of contact with eyes, rinse immediately with plenty of water.
- 

If swallowed, seek medical advice immediately.
- 

Ensure adequate ventilation during application and drying.
- 

Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, heat and moisture.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

- ✓ Fine Woodwork
- ✓ Furniture
- ✓ Decorative Surfaces
- ✓ Artistic Projects
- ✓ Professional Use

HOW TO USE

- 1 Prepare the surface properly.
- 2 Stir well before and during use.
- 3 Apply 2 – 3 coats with drying time between coats.
- 4 For best results, use compatible primer and thinner.

SCAN TO KNOW MORE

