


PUREBASE EXT

PREMIUM EXTERIOR PRIMER

Purebase Ext provides a brilliant, smooth foundation for durable and long-lasting exterior wall finishes.



1. IDEAL FOR



EXTERIOR MASONRY WALLS



FOUNDATION FOR EXTERIOR TOPCOAT APPLICATION

2. FEATURES AND BENEFITS



SUPERIOR SURFACE WHITENESS
Provides excellent opacity and a bright white base for vibrant topcoat shades.



ULTRA-SMOOTH FINISH
Ensures a levelled surface that enhances the final appearance.



MAXIMUM ADHESIVE STRENGTH
Delivers strong bonding with the surface for long-lasting performance.



ENHANCED WALL LONGEVITY
Improves durability and protects walls against weather and wear.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:
Acrylic Based Exterior Primer

PHYSICAL PARAMETERS:

- Colour and appearance: White (Smooth)
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 10 – 12 sq m/L per coat at 25 microns DFT

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	Visual	Smooth Matt
Colour	Visual	White
Solids by Volume	ASTM D 2697	35 – 40%
Specific Gravity	ASTM D 1475	1.30 – 1.45
Touch Dry	ASTM D 1640	30 – 60 mins
Hard Dry	ASTM D 1640	6 – 8 hours
Recoating Interval	-	4 – 6 hours
Application	-	Exterior walls
Coverage	ISO 11890-1	10 – 12 sq m/L per coat

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure the exterior wall is clean, dry, and free from dust, loose particles, or grease.
- Remove any peeling paint, algae or laitance.
- Repair cracks and allow the surface to dry.



APPLICATION

- Stir the primer well before use.
- Apply an even coat using a brush, roller or spray for uniform coverage.
- Allow to dry for recommended time before applying topcoat.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for Purebase Ext for detailed information about safety measures while handling the paint, which is available on request.



Keep out of reach of children and away from eatables.



Do not pour leftover paint down the drain or in water courses.



Store the container with the lid tightly closed, in an upright position, in a cool, dry place.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



In the event of spills, contain spillage using sand or earth.



Wear eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store in a cool and dry place at ambient temperatures.

RECOMMENDED FOR



- ✓ Residential Buildings
- ✓ Commercial Complexes
- ✓ Institutional Buildings
- ✓ Exterior Renovation Projects

HOW TO USE

- 1 Prepare the surface properly. Ensure the exterior wall is clean, dry, and free from contaminants.
- 2 Apply Purebase Ext primer evenly to the surface and allow it to dry.
- 3 Topcoat Finish Once the primer has cured, proceed with your desired exterior topcoat for a durable and long-lasting finish.

