

PureCoat

PREMIUM WALL ENAMEL

Premium Wall Enamel for interior surfaces



WATER BASED



LOW VOC

LOW VOC BENEFITS

- ✓ Low odor & safer indoors
- ✓ Environment friendly

1. AREAS OF APPLICATION



LIVING ROOMS



COMMERCIAL SPACES



HIGH TRAFFIC AREAS



CEILINGS

Ideal for interior walls and ceilings in residential, commercial, and institutional spaces.

2. FEATURES AND BENEFITS



SUPERIOR SCRUB RESISTANCE

Easy to clean and maintain, ensures long-lasting beauty.



ULTRA-MATTE FINISH

Elegant, non-reflective finish that conceals surface imperfections.



EXCELLENT HIDING POWER

Provides uniform coverage with a smooth and even finish.



DURABLE & WASHABLE FILM

Forms a tough, washable film that stands up to daily wear and tear.



ENHANCED COLOR TECH

Advanced pigments for rich, lasting, and fade-resistant colors.



FORMULATED FOR EFFICIENCY

Easy to apply with excellent flow and leveling.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Dispersion Type: Acrylic Copolymer
- Finish: Ultra-Matte ($\leq 3\%$ at 85°)
- Pigment: High Grade Titanium Dioxide

PHYSICAL PARAMETERS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Volume Solids	ISO 3233	42% $\pm$ 2%
WFT (Wet Film Thickness)	Calculated	100 - 120 microns
DFT (Dry Film Thickness)	Calculated	42 - 50 microns
Specific Gravity	ASTM D 1475	1.38 kg/L $\pm$ 0.02
Adhesion	ASTM D 3359	> 2B
VOC Content	US EPA 24	< 15 g/L
Color of Dry Film	Visual	White (tintable)

4. APPLICATION METHOD



SURFACE PREPARATION

- All surfaces must be sound, clean, dry, and free from loose material, dust, dirt, oil, and grease.
- Remove any efflorescence by sanding. New concrete/plaster must be fully cured (minimum 28 days) before painting.
- Fill any imperfections with suitable Acrylic Wall Putty and sand smooth.



PRIMING

- Apply one coat of COLORSOME Water Based Wall Primer at recommended coverage of 8-10 sq.m per liter.
- Allow to dry completely for 2-4 hours.
- Check for dry adhesion before top coating.



APPLICATION

- Ensure paint is thoroughly mixed. Product may be thinned up to 5-10% with clean water if necessary.
- Apply two coats of PureCoat Premium Wall Enamel by brush, roller, or spray.
- Allow 4-6 hours drying time between coats at 27°C .
- Final cure is achieved after 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for comprehensive safety guidelines.



Ensure good ventilation during application and drying.



Wear protective gloves, eye and face protection.



Keep out of reach of children.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately and show container or label.



Dispose of contents/container in accordance with local and national regulations.

STORAGE PRECAUTIONS



- Shelf Life: 24 months
- Store in a cool, dry place away from direct sunlight. Protect from freezing.

HOW TO USE

- 1 Surfaces must be clean and dry.
- 2 Apply 1 coat of COLORSOME Wall Primer.
- 3 Apply 2 coats of PureCoat, allowing time between.
- 4 Enjoy a superior finish.

RECOMMENDED FOR

- ✓ Interior Walls
- ✓ Ceilings
- ✓ Residential Projects
- ✓ Commercial Renovations
- ✓ New Construction



SCRUB RESISTANCE



ULTRA-MATTE FINISH



COLOR TECH



WASHABLE FILM



PREMIUM QUALITY