


Quartz Tex

QUARTZ-BASED TEXTURE FINISH

Elevate your exterior facades with the distinctive, enduring elegance of a premium quartz-textured finish.



PREMIUM
QUALITY



EXTERIOR
DURABILITY



DISTINCTIVE
SWIRL PATTERN

2. AREAS OF APPLICATION



Exterior Walls



Building Façades

FEATURES AND BENEFITS



PREMIUM FORMULATION

Premium acrylic-modified resin ensures excellent adhesion, flexibility and durability.



SPECIAL-GRADE QUARTZ

Contains special-grade quartz particles for superior texture and long-lasting performance.



DISTINCTIVE SWIRL PATTERN

Specially designed texture creates a sophisticated swirl pattern with rich depth.



SUPERIOR AESTHETICS

Offers a refined, high-end finish that enhances the architectural appeal of any structure.

3. PRODUCT DETAILS

DESCRIPTION:

Formulated with high-quality acrylic-modified resin and special-grade quartz, this texture creates a sophisticated swirl pattern. It provides exceptional depth and character while ensuring long-lasting protection for your building's exterior.

FINISH:

Give aesthetic finishing

APPLICATION:

Exterior walls; Façades

TECHNICAL SPECIFICATIONS:

PARAMETER	TEST STANDARD	TYPICAL VALUES
Binder	-	Acrylic Modified Resin
Texture	-	Quartz Swirl
Solids by Weight	ASTM D 1644	72 ± 2%
Drying Time (Touch Dry)	ASTM D 1640	2 – 4 hours
Recoat Time	ASTM D 1640	12 – 16 hours
Water Dilution	-	Ready to use
Coverage	ISO 11890-1	1.0 – 1.5 kg/m ² per coat (Varies with surface texture)
Packaging	-	As per availability
Shelf Life	-	12 months from mfg. date

4. HOW TO APPLY



1 PREPARE SURFACE

Ensure the exterior surface is clean, dry, and free from loose particles or contaminants.



2 APPLY TEXTURE

Evenly spread the Quartz Tex coating over the surface using a trowel to achieve uniform coverage.



3 CREATE PATTERN

Use a specialized tool to work the material into a distinctive swirl pattern before it begins to set.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for detailed safety information before use.



Store the product in a cool, dry place with the lid tightly closed.



Wear appropriate personal protective equipment during application.



In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



Keep out of reach of children and away from eatables.

6. STORAGE PRECAUTIONS



Store in a cool, dry place at ambient temperature. Protect from direct sunlight and extreme heat.

7. RECOMMENDED FOR



- ✓ Residential Buildings
- ✓ Commercial Complexes
- ✓ Institutional Buildings
- ✓ High-End Façade Projects

8. HOW TO USE

- 1 Prepare the surface properly.
- 2 Apply Quartz Tex as per recommended method.
- 3 Allow adequate drying and curing.

SCAN TO KNOW MORE



PREMIUM
QUALITY



EXTERIOR
DURABILITY



DISTINCTIVE
SWIRL PATTERN



WATER-MIX
FRIENDLY